

F00RJ02004 Injector Valve Assembly Technical File

1.6.F00RJ02004 Injector Valve Assembly's Packing List......7 2.F00RJ02004 Injector Valve Assembly Technical Support 2.3.F00RJ02004 Valve assembly Technical Support Obtaining Methods. 3.3.F00RJ02004 Valve assembly's Declaration Requirements10 3.4.F00RJ02004 Valve Assembly's Shipping Ways 10 4.F00RJ02004 Valve Assembly's Storage Standard 12 5.2. Sales-men's Contact Information...... 13

F00RJ02004 Injector Valve Assembly Technical File

NORT.

98⁹³

1. F00RJ02004 Injector Valve Assembly's Introduction

SPARSA

1.1.F00RJ02004 Injector Valve Assembly's Basic Information

State Title and S	China made brand new fuel injector valve assembly F00RJ02004
SKU1	G1Z10F00RJ02004/Z10000B2BJ02004

1.2.F00RJ02004 Injector Valve Assembly's Application Information for Injectors
 (1) F00RJ02004 Injector Valve Assembly's Car Model Matching Information

Injector Part Number	Car Model	OE Number	OE Number	OE Number	OE Number	OE Number	OE Number
0 445 120 050	CUMMINS	3 999 834	3 999 832	3 970 985	and the	at the	×.
0 445 120 071	CUMMINS	3 999 832	4 940 096	3 970 987	an ar	3. ² .000	S.
	CUMMINS	4 988 835	a a				-
0 445 120 161	FORD	BH1X 9K526 CA	all all	and the second	and all all	n star	- 18 C
0 445 120 161	TATA (TELCO)	570107999909					
and the second	TEMSA	4 988 835	and the second	and water	and the same	and wat	5
0 445 120 177	CUMMINS	5 254 261	21. 21.	-20.	SU. SU.	84.	200
0 445 120 184	CUMMINS	4 981 077	1	18 ⁵ . 18 ⁵		15 . 15	5
0 445 120 185	CUMMINS	4 981 076	260 26	Stor.	8340 - 844	Store	Sec.
	CUMMINS	4 983 514	5 256 034	10 10		1 A	-C
0 445 120 187	DODGE	68210 512AA	all all all	ar. Stylar.	ahan ah	e de la companya de l	S.C.
	RAM	68210512AA					_
and the second	CUMMINS	4 994 928	and the second	and another	and the second	part and	and a
0 445 120 188	DODGE	68086 182AA		24	Sec	20.	1.00
a start a	RAM	68086182AA	1	1790. 1790.	a start a	anti santi	1
50°° 50°°	CUMMINS	5 253 220	5253220- NX	500	3m - 3m		48°
0 445 120 193	DODGE	68002 012AA	68069 384AA	68002 012AB	R8069384 AA	68027 067AA	68027 067AB
SAUTORIT SAU	RAM	6806 9384AA	6800 2012AA	6800 2012AB	R8069384 AA	ANT STRAT	r St ^{el}
	CUMMINS	5 253 221					
0 445 120 204	DODGE	9864 35519	68002 012AC	09864 35519	SUPERIOR 214	CALL STREET	St. St.
0 445 400 027	CUMMINS	5 269 194	a .a				e.
0 445 120 267	HINO	89550E0072	all al	an alan	and and	an strau	- 10 ¹⁰
0 445 120 332	CUMMINS	5 262 128					
0 445 120 336	CUMMINS	5 289 380	and the second	and safet	all the second	and and the	
30	CUMMINS	4 994 925	an an	30	34	24.	24.
0 445 120 342	DODGE	68210105-AA	Para Pa	Bar Bar	100	Bar Bar	N

-	RAM	68210105AA	4 994 925				
0 445 120 356	CUMMINS	5 303 101		and a series	- 10 C	1. S. S.	, ,
0 445 120 384	CUMMINS	5 310 954	- Store - Store	35	ar ar	S.C.	\$ ²

SPLODIC SPERSON SHIDAL SPARAC SHEDDE 212.2011 SPREET SHADAT SPREEDST SPREAM SPREED SPREED $\otimes^{[0]}$ SHARAT 2010 P.S. 97^{2,205} al^{ant} SAL SUL SA.^{DA} 98⁹⁹⁰⁰ 98^{,98} States gi^{gi} $S^{(i)}$ SPANDATE STREET SPASIAL SPREAT STATIST SPREAT STRUTT SPREEDENT SPREAT SPREAT SPREEDENT SHATTAR $\phi_{i}^{(k)}$ SPREAT SPR. MONT Y STRATTON SPRINT SPANOSTI SPANNETT SPREAT SPANDATE SPANIST SPREEDENT SPACE SPREAT $\phi_i^{(k)}$ SPAIRSTY SPALEDATT SPAUDONT SPR. SPATT SPARATT SPERAT SPREAT REPORT SPECTAL SPASSON . 570.200 T 51020205 $\varphi_i^{(0)}$ SAUDATI SPURATE SPLEAT SPLEENT SPREAT SPUDEN SPERIOT SPANIST SPERIAL SPLIDET SPRIMENT Stard Stard $\wp^{(i)}$ SPURATE SHUDER SPARST SPERAT SPEIDER SPEEDAT SPLEET SPATIA SPLEET - Alexandri $\otimes^{(0)}$ STUDIET STUDIE SPORT SHLEEPT SPERAT SPACE SPARAT SPLERAT SPERAL SPERSON SPLEAST SPACE $\oplus^{(0)}$ STRATT SPATIST STREET STRUET SPACE SPLEIT S. A. Barris SPREAT 579,503,77 SPREAT 21/2.2757 gi^{gi} STREET SPARENT SPRETORY SAMATI SPREAME SPRENDERT SPANIE SPRINT SPREAT SPREAT 51937055 sterner. $\phi_{i}^{(0)}$ STRUMPST SPATTER SPANDER SPREEDWI SPR. MINT SPARTER 19.000 M SPRINGER SPERAR SPREEDER SAUSSE 21922222 $\phi_{i}^{(j)}$ SPANOST SPAINST SAUDATI SPARAT Station of SPACES N 372.57.87[°] SPREAT SPECTRO SPERMENT SPERMENT SASSIN $\wp_{i}^{(0)}$ SHUDDER shumer Starrent SPERMENT SPURPI SR.SP. SPATIAN 39.55 anonei 519.507F $\wp^{(0)}$ SPERANT SPLORT SHERRE SPRESS SAUDAT SPERIO SPRENT SPLEINE 518-5097 SPERAT SHADAT SHOWAT $\otimes^{\mathbb{N}}$ States C SPERMIT SPREAT SPERSON SPATIST SPATIAN SPLEINT SPERANT SHAMPY SPLEET 512-557 SPARINT $\otimes^{[0]}$ SPARAT SPERMENT STRATT STATIST SPARAT SPLETSTE SPREDENT SPREAM SPREME SPLEET SPREAT SHARTSTE $\phi^{(0)}$. and the . with Ci and^{ar (1} . and the . and . 188²⁵



(2) F00RJ02004 Injector Valve Assembly's Application for Injectors' Part Number

Injector Series	Injector Part Number	System Pressure	Re-manufactured Part Number	System Pressure	Universal Number	System Pressure	Universal Number	System Pressure
	0 445 120 050		0.096.425.519	1900	0 445 120		0 445 120	1800
CRIN3-18	0 445 120 050		0 986 435 518	1800	185		193	1000
CRIN3-18	0 445 120 071		0 986 435 519	1800	0 445 120	1800		
	0 443 120 07 1		0,000,435,517	1000	204	1000		
CRIN3-18	0 445 120 161	1800	0 986 435 645					
CRIN3-18	0 445 120 177	1800						
CRIN3-18	0 445 120 184		0 986 435 519	1800	0 445 120	1800		
CRIN5-16	0 445 120 184		0 980 433 319	1800	204	1000		
CRIN3-18	0 445 120 185		0 986 435 518	1800	0 445 120	1800		
	0 110 120 100		0,000,100,010	1000	193	1000		
CRIN3-18	0 445 120 187	1800 187	0 986 435 573	1800	F 00E 200			
					419			
CRIN3-18	0 445 120 188	8 1800	0 986 435 574	1800	F 00E 200			
					420			
CRIN3-18	0 445 120 193	1800	0 986 435 518	1800				
CRIN3-18	0 445 120 204	1800	0 986 435 519	1800				
CRIN3-18	0 445 120 267	1800						
CRIN3-18	0 445 120 332	1800						
CRIN3-18	0 445 120 336	1800						
CRIN3-18	0 445 120 342	1800	0 986 435 621	1800				
CRIN3-18	0 445 120 356	1800						
	Stop. Stop.	38 ²⁹¹¹ 38 ²³	21820 - 21820 - 21820	stor s	the strain :	an an	32 ⁸¹	

Mob/Whatsapp: +86 13410541523 Email : ruby@shumatt.com Tel: +8675523215133 Website : www.shumatt.com

© 2022 Shenzhen Shumatt Technology Co., Ltd

4 / 14

01 00 00

-03-55

CRIN3-18	0 445 120 384	1800	0 986 435 644					
	Style Style	SIR.500 SIR.5	10. 218-20. 218-20. 24	station of	him. Strin	Star 200 .	States - Sta	
	STANDATT STAND	TT SPRADDATT SPRA	SALT SHARANT SHARATT SH	JOHN SALDAN S	ASCALL SPASS	SPARATE	SHADDATT SHE	
	SPECTOR SPECTO	TT SPARATT SPAT	SALT SPORTT SPORTT SP	and seaming	NUMER CAN	TI SPARATI	SHADDALL SHE	
	SHUMPI' SHUMP		SALL SPERAL SPERAL SP	State Streams	AUDINT' SHUDD	SPLEINT,	SPREMATT SPR	
	States States				NUMER SHOP			
	STUDIN'S STUDI				AURIST SHARE			
	Stormer Storm				AUDIT SPADS			
	SHARPETT SHARP				AJERST' SPAJE			
	SHAMPY'S SHAMP				AUDITT SPADD			
	SHUMPIT'S SHUMP				ASDALL SHOW			
	SHUDDI'S SHUDD	17 SHADATT SHAD	and statem statem at	PART SPERAL S	ADDALL SHOOD	SHARATT	SPREAMENT SPRE	
	SHADALL	17 SHEADAN SHE	ant' stampt stampt st	SPECIAL SPECIAL	NUME SPOR	SHERRE	SHRATT SHR	

 $\otimes^{[0]}$

© 2022 Shenzhen Shumatt Technology Co., Ltd

Strant.

 $S^{0,r}$

(3) **F00RJ02004** Injector Assembly Part Number Common Writing

F00RJ02004, F00RJ02004, F 00R J02 004, F 00R J02 004, F00R J02 004, F00R J02 004, F00R J02 004, F00R J02004, F00R J02004,

1.3.F00RJ02004 Injector Valve Assembly's Specifications and Dimensions Parameters

Valve Assembly Size: 13 cm*2 cm *2 cm

Valve Assembly Box Size: 14 cm *3 cm *3 cm

Valve Assembly Packing Size: 31 cm *12 cm

Valve Assembly Net Weight: 0.03kg

Valve Assembly Gross Weight: 0.03kg

Valve Assembly Quality: China Made Brand New Injector Valve Assembly

Valve Assembly MOQ: 4 PCS

1.4.F00RJ02004 Injector Valve Assembly's Quality Control

(1) Valve Assembly Testing

All parts of the injector valve assembly are subjected to precision testing, high temperature testing, low temperature testing, withstand pressure testing, leakage testing, durability testing, and various working conditions testing.

(2) Injector Valve Assembly Inspection

The factory inspection of the injector valve assembly is undergone full inspection, random inspection, and batch inspection three inspections. Different brands of test benches are used to test the same injector valve assembly for a total of no less than three times for factory inspection, and the fuel injector installation testing environment are progressed in dust-free workshop.

(3) Injector Valve Assembly Installation

When matching the valve cap and valve steam, Shumatt strictly complies with the standard of valve cap and valve stem clearance technical indicators to ensure that each valve assembly meets the factory standards and use standards.

1.5.F00RJ02004 Injector Valve Assembly's Customized Service

(1) Valve Assembly's Customized Service: Meet the customized needs of OEM manufacturers for shell lettering, logo engraving, injector internal packaging, injector external packaging and labels customized, etc.



Mob/Whatsapp: +86 13410541523 Email : <u>ruby@shumatt.com</u> © 2022 Shenzhen Shumatt Technology Co., Ltd



(2) Valve Assembly's Customized Service Requirements:

Customized valve assembly box are no less than 100 pieces.

Customized valve assembly groove no less than 100 pieces.

The purchased of customized valve assembly are no less than 1000 pieces.

The purchased of customized valve cap engraving contents are no less than 1000 pieces.

The purchased of customized valve colors are no less than between 1000 -10000 pieces.

Customized products involve the need of specify logo, the OEM manufacturer needs to provide trademark authorization and the sample of logo image file.

A Once the customized injector valve assembly is sold, it can not be returned or exchanged if there is no quality problems.

1.6.F00RJ02004 Injector Valve Assembly's Packing List

	Assembly's spare parts list	and the second	and a start a start as start and
Serial Serial Number	31 31 31 31 1	2 31° 31° 31°	30. 31. 31. 31. 31.
STANDING STA	and the shame	STRUTT STRUTT	ert at fait
Stutter St	and the second s	all ^{all} are are all ^{al}	
Name	Injector Valve Assembly	Valve Assembly Anti-rust Paper	Valve Assembly Box (Square is optional)
Description	Valve Assembly Part Number F00RJ02004	Prevent the valve assembly from rusting	Protect the valve assembly from being damaged by colliding
Serial Serial Number	4	5 ST 5	Str. Str. St. St.
SHUTIATT SH Image SHUTIATT SH			ALL SHOWLL SHOWLL SHOWLL SH
Name	Valve Assembly Box (Cylindrical is optional)	VCI Anti-rust Bag	AT WEATH WARDS WEATH AND
Description	Protect the valve assembly from being damaged by colliding	Prevent the valve assembly from rusting	

Minors are prohibited from using the injector valve assembly, valve assembly anti-rust paper, valve assembly box, and VCI anti-rust bag to avoid personal injury.

The valve assembly box is recyclable and can be reused.

VCI anti-rust bag is non-degradable material, please dispose of it properly after use.

1.7.F00RJ02004 Injector Valve Assembly's Warranty Instructions

(1) . Valve Assembly Warranty Conditions and Instructions

It is necessary to provide pictures, videos, or test reports detected by the injector valve assembly inspection equipment when the valve assembly is abnormal during use as evidence to feed back to the

salesman.

Abnormal conditions are properly explained such as: 1.Smoke, 2. Engine shake, 3. Difficulty starting States -28-18⁷⁸ the engine, 4. Engine noise, 5. oil leakage etc.

(2) . Valve Assembly Warranty Coverage

Within 15 days after customer receives the FOORJ02004 injector valve assembly, if there is a performance failure and the product has no appearance damage, customer can choose to replace it or The repair it; 15 N

de la

10 a

100

If the F00RJ02004 injector valve assembly has performance problems during the warranty period (3 months), and it is confirmed that it is product's problems after testing, you can contact our salesmen to replace the same model or a reworked product with the same performance for free; de Ca

If the injector house has obvious scratches, it can only be repaired and it will be returned as it is if the product is confirmed to be fault-free. Then Then

STREET. and a contract and the STORY .

(3) . Injector Valve Assembly Out of Warranty Coverage The warranty period has avoired

The warranty period has expired.

Injector valve assembly failure caused by high temperature, high pressure, humidity, rain and snow, saline-alkali land, earthquake, and used in abnormal environment.

Injector valve assembly damage caused by man-made reasons (throwing, strong magnetic field AND RAN magnetization, set fire). all all all all 33⁹⁹⁴

Injector valve assembly failure or injector damage caused by non-injector design, technology, manufacturing, quality and other issues.

Injector valve assembly failure due to system pressure exceeding system approved pressure.

Injector valve assembly failure caused by system voltage exceeding approved voltage.

Injector valve assembly failure caused by impurities (water, lead, aluminum powder, iron powder, sulfide) in the system fuel exceeding the standard requirements.

Injector valve assembly failure caused by not installing according to the tightening torque specified in the vehicle engine maintenance manual (the tightening torque is too large or too small).

Injector valve assembly failure caused by not following the installation angle specified in the injector maintenance manual.

Injector valve assembly failure caused by not following the cleaning requirements specified in the injector maintenance manual.

Injector valve assembly failure caused by failure to replace consumable parts as specified in the STRATT injector maintenance manual. 39.00

1.8.F00RJ02004 Injector Valve Assembly's Manufacturer


Injector Valve Assembly's Manufacturer: Shenzhen Shumatt Technology Co.,Ltd

2.F00RJ02004 Injector Valve Assembly Technical Support

2.1.F00RJ02004 Injector Valve Assembly's Installation Precautions

- -5A-157F to make the stains, dust, rust-proof oil oxides, paraffin base, naphthenic base, intermediate base, salt, lead naphthenate, zinc naphthenate, sodium netrolection is the state of the state Clean the injector valve assembly in an ultrasonic cleaner for 3-5 minutes before installation, so as sulfonate, calcium petroleum sulfonate, tallow diamine trioleate, rosin amine on the surface of the valve assembly fall off. 100 de. 120 100 d Chi 10 B
- (2) Use compressed air to clean the cleaning fluid attached to the surface of the valve assembly after cleaning, and clean it up to the standard of use, as below , and Transf

Mob/Whatsapp: +86 13410541523 Email : ruby@shumatt.com © 2022 Shenzhen Shumatt Technology Co., Ltd



If the injector steel ball and the ball seat are not installed in accordance with the standard, it may cause serious damage to the injector valve assembly

2.2.F00RJ02004 Injector Valve Assembly Replacement Conditions

(1) Valve Cap

Under the microscope, magnify 20 times to check that the oil inlet hole of the valve cap and the oil return hole of the bonnet are not worn, grooved, scratched, damaged, rusted or dented.




inject oil

68⁵⁸ The side inlet hole is blocked causing the injector to establish the pressure chamber and the injector to function normally

A Wear of the cap cavity can cause the injector to work properly when the injector is badly delayed.

(2) Valve Rod

Microscope amplification 20 times, check the valve rod for wear, not smooth surface color, rust



replaced

▲ The excessive clearance between the stem wear and the housing and between the cap causes an injector delay

▲ The valve stem lag will cause the injector to start the solenoid to start, and the oil needle can not return quickly after the nozzle is opened

A Check the injector components before replacing the injector valve assembly according following the injector service manual to avoid further damage to the injector valve assembly.

2.3.F00RJ02004 Valve assembly Technical Support Obtaining Methods

- Valve assembly Technical file, visit <u>http://shumatt.com</u> to get the technical File
 Injector Technical Videos
- Facebook:
 Visit https://www.facebook.com/hison.li constantly follow can get more information.

 YouTube:
 https://www.youtube.com/channel/UCByvYBx7VjV mAfxh Hu-aw to get the technical videos, constantly follow can get more information.

Shumatt: Visit <u>http://shumatt.com</u> to get the technical videos.

(3) Valve Assembly Information Query Software

TruckBook Parts EPC APP, Android/Apple App Store download and install, visit <u>http://shumatt.com</u> to get the download and installation tutorial

(4) Search The valve assembly test data through TruckBook Parts EPC APP.

3.F00RJ02004 Valve Assembly's Purchase and Delivery.

3.1.F00RJ02004 Valve Assembly Purchase Payment Terms

Payment Terms: T/T, PayPal, Alipay, WeChat

Please contact our salesmen for specific payment information.

3.2.F00RJ02004 Valve assembly's Main Sales Market.

Valve assembly main sales markets: Asia, Europe, North America, South America, Africa etc.

3.3.F00RJ02004 Valve assembly's Declaration Requirements

Shumatt can assist customers to provide the following documents for import customs clearance: contract, invoice, packing list, bill of lading, insurance policy, certificate of origin, etc.

3.4.F00RJ02004 Valve Assembly's Shipping Ways

Destination in China areas: SF Express, Debon Express, the corresponding logistics company can be provided according to customer requirements in special cases.

Destinations out of China's areas: DHL, UPS, FedEx, TNT air, ocean or other shipping methods required by customers.

3.5.F00RJ02004 Valve Assembly's Lead Time

Lead time: Send out within 3 - 7 working days after receiving payment (Except for special products and special cases).

3.6.F00RJ02004 Valve Assembly's Logistics Time for Destination Out of China's Areas

 $\mathcal{G}^{0,2}$

SHUMATT **DHL Logistics Time:**

Country or Region of Departure	Hong Kong, China	Other Countries or Regions of Asia	Australia and New Zealand	Europe	America	Other Countries
China's Mainland	7 Days	7 Days	8 Days	8 Days	8-12 Days	7-10 Days

Country of Destination	Estimated Arrival Time	Country of Destination	Estimated Arrival Time	Country of Destination	Estimated Arrival Time
Japan	3 Days	UK	5-7 Days	Egypt	5-7 Days
Turkey	5-7 Days	Singapore	3 Days	Switzerland	5-7 Days
Bahrain	5-7 Days	Latvia	7-10 Days	New Zealand	7-10 Days
Sri Lanka	5-7 Days	Thailand	3 Days	Austria	5-7 Days
Romania	5-7 Days	Vietnam	3-5 Days	Estonia	5-7 Days
Malaysia	3-5 Days	Israel	5-7 Days	Mexico	7-10 Days
France	5-7 Days	America	5-7 Days	United Arab Emirates	5-7 Days
Italy	5-7 Days	Netherlands	5-7 Days	Bengal	7-10 Days
Lebanon	5-7 Days	Philippine	3-5 Days	Greece	7-10 Days
South Korea	3 Days	Spain	5-7 Days	Myanmar	5-7 Days
Canada	5-7 Days	Germany	5-7 Days	Saudi Arabia	7-10 Days
Portuga	5-7 Days	Australia	5-7 Days	South Africa	7-10 Days
Denmark	5-7 Days	Belgium	5-7 Days	Ukraine	7-10 Days
Stor India Stor	7-10 Days	Qatar	7-10 Days	Poland	5-7 Days
Indonesia	3-5 Days	Morocco	7-10 Days	Pakistan	7-10 Days
Kuwait	7-10 Days	the state states	all all	All All all	an anter

The logistics time is for reference only, subjects are according to the actual arrival.

3.7.F00RJ02004 Valve Assembly's Packing

Domestic express packaging: Usually wrapped in waterproof scotch tape, such as picture No.2. International express packaging: Wrapped with waterproof yellow tape After wrapping the black SAL TR CALES! CALLON -1913 (P) ar.190 protective film, such as picture No. 3.


Pallet Shipping: Use fumigation free and recycling trays that meet export requirements, and use white wrapping protective film to wrap and bind with cable ties for the outside, such as picture No. 4, Also, the products can be packaged according to customers' requirements. -31.50

The packing tray is made of plastic and can be recycled.

and in 9595⁷⁵ A Transparent tape, yellow tape, black wrapping protective film, white wrapping protective film are non-degradable materials, please dispose of them properly.

Minors are prohibited from using transparent tape, yellow tape, black wrapping protective film, and white wrapping protective film to avoid personal injury.





Pic No.2 Domestic express packaging: Wrapped by Transparent tape

Pic No.3 International express packaging: Wrapped with yellow tape after wrapping black protective film





Pic No.4

Pallet Shipping: Use pallet that meet export requirements, and use white wrapping protective film to wrap and bind with cable ties

-ALTERT SHURDER . 4.F00RJ02004 Valve Assembly's Storage Standard

(1) Choose a suitable storage place

The warehouse and cargo yard where the fuel injector is stored should be kept clean and dry, and away from the factory buildings that generate harmful gases and dust; do not mix with acid, alkali, salt and other substances; the storage place should have a good drainage system; the cargo yard should be flattened with gravel or furnace ash etc. to enhance the water permeability of the surface layer to keep the reservoir area dry.

at 194

(2) Strict requirements of warehousing

at the Strict inspections should be carried out when the fuel injectors are put into storage, the surface cleaning work should be done well to remove water traces, oil stains, ash and other dirt, remove the rust and do anti-rust treatment in time. Packaged injectors must be protected from damage.

155

(3) Keep the warehouse dry and preventing moisture

The relative humidity is usually below 70% for the fuel injectors placed in the room, and the corrosion of the fuel injectors is significantly reduced.

Injectors must be stored in the warehouse, and they are forbidden to store in the same warehouse with commodities with high water content. and and and and and and

(4) Stack Properly

Mob/Whatsapp: +86 13410541523 Email: ruby@shumatt.com © 2022 Shenzhen Shumatt Technology Co., Ltd

After the injector is exposed to rain, the corrosion rate will increase significantly. The purpose of sealing is to isolate the injector from rainwater and humid air, so the warehouse window should be checked in time to avoid rainwater entering the warehouse

If the fuel injector package is damaged, it should be repaired or replaced; when the package is damp, the packaging material should be dried; if the original anti-corrosion and oil applied at the factory is found to be damaged or dried up, it should be cleaned and re-applied oil in time.


It is forbidden to leave the injector exposed in the air for a long time.

It is forbidden to store acid, alkali, salt and other substances together with the injector.

The unpacked fuel injector must be rust-proof during secondary storage.

5. Company Information

 3^{0}



Email: ruby@shumatt.com

Website: www.shumatt.net

Shenzhen Office: 11-12, Floor 14, Building 13, Qinchengda Building, Exit A, Honglang North Subway Station, Bao'an District, Shenzhen, China's Mainland

Shenzhen Office: Room 428-430, Building B, Huafeng Zhigu Technology Industrial Park, Exit B, Fuyong Metro Station, Bao'an District, Shenzhen, China's Mainland

Hong Kong Office: Jianfa Street Industrial Zone, Tuen Mun, New Territories, Hong Kong, China

After-sales Service Address: Please contact our salesmen to obtain and provide the corresponding product maintenance reasons (Reference: <u>1.7. F00RJ02004 Injector Valve Assembly's Warranty Instructions</u>)

5.2. Sales-men's Contact Information

Mob/Whatsapp: +86 13410541523 Email : <u>ruby@shumatt.com</u> © 2022 Shenzhen Shumatt Technology Co., Ltd Tel: +8675523215133 Website : www.shumatt.com

1	Ruby	+86-13410541523	ruby@shumatt.com	Hison Li	Hison Li
2	lvy	+86-18025309821	sales@shumatt.com	Ivy Shumatt	Shumatt IVY
3)(Rebecca	+86-18025349821	sales01@shumatt.com	Rebecca SHUMATT	SHUMATT Rebecca
4	Janny	+86-18028749821	sales02@shumatt.com	Janny shumatt	Janny Shumatt
5	Sam	+86-13316859821	Sales8@shumatt.com	Shumatt Sam	Sam Shumatt
6 . 3	Natalie	+86- 18938945856	sales15@shumatt.com	Shumatt Natalie	Lin Natalie
7	Ada 🖌	+86-1342286353	sales5@shumatt.com	Shumatt Ada	Ada Shumatt
8	Hison Li	+86-18318811871	web@shumatt.com	Hison Li	Hison Li
9	Mecca	+86-18938948618	sales11@shumatt.com	Shumatt Mecca	Shumatt Mecca
10	Eric	+86 18319033618	sales3@shumatt.com	de de	100 100
11	Wayne (Joaquín en español)	+86-13316959821	wayne@shumatt.com	shumattwayne	Wayne Shumatt
12	Sylvia	+86 18312499884	sales6@shumatt.com	n - 192 - 19	and the second

6. Copyright Statement

The copyright of any contents "FOORJO2004 valve assembly technical file" (including but not limited to parameters, data, text, charts, images, sounds or videos, etc.) provided in "FOORJO2004 Valve assembly Technical File" belong to Shenzhen Shumatt Technology Co., Ltd. Without the prior written permission of Shenzhen Shumatt Technology Co., Ltd., you are not allowed to modify any contents in "FOORJO2004 Valve assembly Technical File" in any way. At the same time, any conditions to spread, re-post, display the contents of "FOORJO2004 Valve assembly Technical File" should indicate that the cited article is from Shenzhen Shumatt Technology Co., Ltd., Any actions failure to follow above conditions to use "FOORJO2004 Valve assembly Technical File" will violate the "Copyright Law of the People's Republic of China" and other laws and regulations and the provisions of relevant international conventions.

5.^{9,208}

A.S

 $\otimes^{\mathbb{N}}$

Mob/Whatsapp: +86 13410541523 Email : <u>ruby@shumatt.com</u> © 2022 Shenzhen Shumatt Technology Co., Ltd Tel: +8675523215133 Website : www.shumatt.com