320D Injector 32F61-00014 Technical File SKU:G2C632F6100014 PAR 26 320D INJECTOR 3264700 **INJECTOR**

SHUMATI

SPUDIOT

SPARST

SPARANT

320D Injector 32F61-00014 Technical File SPREAT

SPERMET

SHARSHIT

 $-\phi h^{(0)}$

 $\otimes l^{(i)}$

 $= \otimes^{[0]}$

an success success

1. 32F61-00014 Injector Introduction1
1.1. 32F61-00014 Injector Basic Information
1.2. 32F61-00014 Injector Common Part Number1
1.3. 32F61-00014 Injector Part Number Common Writing
1.4. 32F61-00014 Injector Parameter1
1.5. 32F61-00014 Injector Specifications and Dimensions1
1.6. 32F61-00014 Injector Quality Control1
1.7. 32F61-00014 Injector Customized Service2
1.8. 32F61-00014 Injector Packing List and Package Size
1.9. 32F61-00014 Injector Testing Standard and Certificate4
1.10. 32F61-00014 Injector Warranty Instructions4
1.10. 32F61-00014 Injector Warranty Instructions
2. 32F61-00014 Injector Technical Support5
2.1. 32F61-00014 Injector Part Number Location5
2.2. 326-4700 Injector Application Scenarios
2.3. 32F61-00014 Injector Installation7
2.4. 32F61-00014 Injector Reasons of Not Working Normally
2 = 22 E(1, 00014) Injector Courses to Domogo
2.5. 32F61-00014 Injector Causes to Damage 2.6. 32F61-00014 Injector Technical Support Obtaining Methods
3. 32F61-00014 Injector Purchase and Delivery9
3.1.32F61-00014 Injector Purchase Payment Term
3.2. 32F61-00014 Injector Main Sales Markets9
3.3. 32F61-00014 Injector Declaration Requirements9
3.4. 32F61-00014 Injector Shipping Ways
3.5. 326-4700 Injector Lead time9
3.6.32F61-00014 Injector Logistics Time for Destination Out of China's Areas9
3.7. 32F61-00014 Injector Packing
4. 32F61-00014 Injector Storage Standard
5. Company Information
5.1. Company Introduction
5.2. Contact Information
6. Copyright Statement
the
and the second

ALL SHEART SHE

320D Injector 32F61-00014 Technical File

1. 32F61-00014 Injector Introduction

1.1. 32F61-00014 Ir	njector E	Basic Info	ormation	ra Sta	NORT -	ware .	WEER.	ALTON .	ALTER .	States and
Title	C	china mac	le new 3	20D inje	ector 32F6	51-00014	l fuel inj	ector for	C4.2 Eng	ine
SKU 1			15	100	G2C632	F610001	4	and the	. and	

1.2. 32F61-00014 Injector Common Part Number

(1) Injector Exchange Information

Injector Part Number	Re-manufactured Number	Part	Replacement Number	OE Number		
32F61-00014	10R-7951	100	326-4756	32F61-00014		
32F6100014	10R7951	9 9	3264756	32F6100014		

(2) 32F61-00014 Matching Information

Car Model	Engine	Engine	Engine	Engine
EXCAVATOR	311D LRR	312D	314D CR	314D LCR
SHUMPLY SHUMPY	312D L	313D 313D	320D	320D L

1.3. 32F61-00014 Injector Part Number Common Writing 32F61-00014, 32F6100014, 10R-7951, 10R 7951, 10R 7951, 326-4756, 326 4756, 3264756

1.4. 32F61-00014 Injector Parameter

Adaptation System: Common Rail System

Injector Series: 320D C4.2 Series

Injector Type: Electromagnetic Injector Vehicle Configuration Information: 320D Engines

1.5. 32F61-00014 Injector Specifications and Dimensions Injector Size: 20cm* 10cm *10cm =2000cm³ (L*W*H=V)

Injector Net Weight: 0.5kg

Injector Gross Weight: 0.55kg

Injector Quality: China Made New

Package Size: 22 cm* 13 cm *13 cm = 3718 cm³ Injector Type: Diesel Common Rail Injector

100 C

MOQ: 4 Pieces

1.6. 32F61-00014 Injector Quality Control

(1) Injector Testing

65 All injector spare parts are tested for electrical characteristics, accuracy, high temperature, low temperature, withstand voltage, leakage, durability, and various working conditions. Star. all the and the

(2) Injector Assembling

And the quality control of the injector production and installation process, our company strictly follows the standard product installation data and product installation steps to install, such as injector stroke test, injector solenoid valve tightening torque, injector nozzle tightening torque.

(3) Injector Inspection

The factory inspection of the injector is undergone full inspection, random inspection, and batch

inspection three inspections. Different brands of test benches are used to test the same fuel injector for a total of no less than three times for factory inspection, and the fuel injector installation testing environment are progressed in dust-free workshop.

1.7. 32F61-00014 Injector Customized Service

(1) Injector Customized Service: Meet the customized needs of OEM manufacturers for shell lettering, logo engraving, injector internal packaging, injector external packaging and labels customized, etc.



(2) Injector Customized Service Requirements:

The purchased of customized injector are not less than 10 pieces.

Customized injector packages no less than 1000 pieces.

Customized products involve the need of specify logo, the OEM manufacturer needs to provide trademark authorization and the sample of logo image file. A Once the customized fuel injector is sold, it cannot be returned or exchanged if there is no quality

problems.

1.8. 32F61-00014 Injector Packing List and Package Size

(1) Injector Spare Parts List

No.	1	2	3
20, 20,		21. 21. 21. 21	
STANDING STAND		ant success of a success of	and the second sec
Strand, Stran	TT SHERT CONT SHERT SH	Salar Shasan Share Shasan S	ATTACT SHATTATT SHATTATT SH
Name	Fuel Injector	O-Ring	Nozzle Protective Cover Cap
Description	Fuel injector part number 32F61- 00014	Ensure to meet the standard of the sealing performance between the injector and the engine	Protect nozzle holes from being polluted and blocked
No.	4	5	6

Mob/Whatsapp: +86 13410541523 Email :<u>ruby@shumatt.com</u> © 2023 Shenzhen Shumatt Technology Co., Ltd

SHUMMIT Image SHUMMIT SHUM			
Name	Injector Oil Inlet Tube Cap	Solenoid valve protective cover	VCI Anti-rust Bag
Description	Protect oil inlet from being polluted and blocked	Protect the solenoid body and terminal posts from external forces	Prevent fuel injector from rusting
No.	7	8	9
Image		SHUMATT	
St Names 10	Bubble Bag	Injector Packing Box	Nozzle Gasket
Description	Prevent the injector from being damaged by external forces	Package for injector and injector accessories	Used to ensure the tight fit between the tight cap end of the injector and the engine

Minors are forbidden to use the fuel injector assembly, O-ring, gasket, nozzle protective cover, fuel injector house protective cover, solenoid valve protective cover, VCI anti-rust bag, and air bubble bag to avoid personal injury.

O-ring and gasket are disposable installation accessories, and need to be replaced for re-installation.

The nozzle protective cover, the injector house protective cover, and the solenoid valve protective cover are recyclable accessories that can be reused.

VCI anti-rust bags and bubble bags are non-degradable materials, please dispose of them properly after using.

 $oldsymbol{\Lambda}$ The injector and the installation parts should be coated with appropriate sealing oil during

installation. האינימאל אינימאלי אינ

(2) Injector Box Size and stand stand

SANDALL SANDALL

1.50

Mob/Whatsapp: +86 13410541523 Email :<u>ruby@shumatt.com</u> © 2023 Shenzhen Shumatt Technology Co., Ltd Tel: +8675523215133 Website : www.shumatt.com

3 / 15



NO.	Name			In	jector	Package Siz	e (cm)				6
3.1 ⁰⁰⁰	Injector Box	A. Starrey	A.	de alter	all all	22*13*13	SAL PROPERTY	A.S.	Aller	2200	58 ²⁶ -
_											201

1.9. 32F61-00014 Injector Testing Standard and Certificate

We can provide the factory quality inspection test report of each injector to ensure that each injector delivered meets the engine performance indicators.



1.10. 32F61-00014 Injector Warranty Instructions

SPANSFIC SPECTO (1) Product Warranty Conditions and Instructions It is necessary to provide pictures, videos, or test reports detected by the injector inspection equipment when the injector is abnormal during use as evidence to feed back to the salesman. Abnormal conditions are properly explained such as: 1.Smoke, 2. Engine shake, 3. Difficulty starting the engine, 4. Engine noise, 5. oil leakage etc. THE THE THE THE STATE STATE STATE STATE

(2) Injector Warranty Coverage

Mob/Whatsapp: +86 13410541523 Email :ruby@shumatt.com © 2023 Shenzhen Shumatt Technology Co., Ltd

Within 15 days after customer receives the **32F61-00014** injector, if there is a performance failure and the product has no appearance damage, customer can choose to replace it or repair it;

If the **32F61-00014** injector has performance problems during the warranty period (6-12 months), and it is confirmed that it is product's problems after testing, you can contact our salesmen to replace the same model or a reworked product with the same performance for free;

If the injector house has obvious scratches, it can only be repaired and it will be returned as it is if the product is confirmed to be fault-free.

Tips: For products not covered by warranty, our company can provide paid maintenance services. For products after paid repaired, the same performance problem will have a free warranty period within 3 months from the date of repairing.

(3) Injector Out of Warranty Coverage

The warranty period has expired.

Injector failure caused by high temperature, high pressure, humidity, rain and snow, saline-alkali land, earthquake, and used in abnormal environment.

Customer disassembles or repairs the injector personally resulting in damage to the injector.

Injector damage caused by man-made reasons (throwing, strong magnetic field magnetization, set fire). Injector failure or injector damage caused by non-injector design, technology, manufacturing, quality and other issues.

Injector failure due to system pressure exceeding system approved pressure.

Injector failure caused by system voltage exceeding approved voltage.

Injector failure caused by impurities (water, lead, aluminum powder, iron powder, sulfide) in the system fuel exceeding the standard requirements.

Injector failure caused by not installing according to the tightening torque specified in the vehicle engine maintenance manual (the tightening torque is too large or too small).

Injector failure caused by not following the installation angle specified in the vehicle engine maintenance manual.

Injector failure caused by not following the cleaning requirements specified in the vehicle engine maintenance manual.

Injector failure caused by failure to replace consumable parts as specified in the vehicle engine maintenance manual.

Injector failure caused by not complying with the intake system fit clearance and exhaust system fit clearance requirements specified in the vehicle engine maintenance manual.

Failure to replace the consumable parts and the fitting clearance of the oil inlet system pipeline and the fuel injector connection in accordance with the fuel intake system specified in the vehicle engine maintenance manual.

1.11. 32F61-00014 Injector Manufacturer


Injector manufacturer: Shenzhen Shumatt Technology Co., Ltd


2. 32F61-00014 Injector Technical Support

2.1. 32F61-00014 Injector Part Number Location

There There I there I there a second a second secon

1) E.g.: The injector part number see as follows

Mob/Whatsapp: +86 13410541523 Email :<u>ruby@shumatt.com</u> © 2023 Shenzhen Shumatt Technology Co., Ltd 



 $\varphi_{i}^{(p)}$


2.2. 326-4700 Injector Application Scenarios



STRUMPT

STRIPPET

Matching Car Model: Caterpillar 320D excavator



Mob/Whatsapp: +86 13410541523 Email :<u>ruby@shumatt.com</u> © 2023 Shenzhen Shumatt Technology Co., Ltd

No.	Name	No.	Name	No.	Name
1	Adaptor Fixing Bolt	2	Gasket	ра 13 13	Fuel Injection Adaptor
State -	Fuel Injector	్ 5 ్లో	Injector O-Ring	6 3	Injector Nozzle Gasket
7.5 -63	Intake Gasket	8	Intake	91	High Pressure Common Rail Pipe

2.3. 32F61-00014 Injector Installation

(1) 32F61-00014 Injector Installation Precautions:

STATIST ment of the fuel interior SPRINT f A The replacement of the fuel injector must strictly follow the electrical system, the approved pressure of the low-pressure fuel intake system, the approved pressure of the high-pressure fuel circuit system, and fuel system replacement consumables requirements (including the low-pressure fuel circuit system filter and the high-pressure fuel circuit) specified in the vehicle engine maintenance manual;

Replacement of wearing parts of the fuel system, cleaning requirements for the connection between the fuel system and the injector, the fitting clearance of the fuel injector connection, the installation angle and tightening torque of the injector, the fitting clearance of the intake system, and the fitting clearance of the exhaust system to ensure the service life of the engine and the normal operation of the injector.

A When installing the fuel injector on the engine, it is necessary to clean the engine block, cylinder head and other parts connected to the fuel injector, and ensure that there is no dust, carbon deposits, water, rust spots, etc.

ant^{ra} all^{er} STATE and a start a start a start a start a all a Before installing, check whether the fuel injector nozzle gasket has been replaced and installed on the fuel injector.

STREET. A-STREEMENT TT SPERATT SPERATT SP ST SALEST SALEST SALEST STREETS T - A.10 A When installing the fuel injector, apply lubricant between the fuel injector, fuel nozzle sealing gasket SALENT SALENT SALENT SALENT'S

A Without replacing new gasket can lead to: deformation of the tight cap of nozzle, deformation of nozzle, deformation of nozzle orifice, oil leakage and air leakage, which will cause serious damage to the fuel injector and nozzle to break and cause damage to the engine. TEN . and a call a call a call a call a call a call

When installing the injector on the engine, please carefully check the components related to the installation of the injector, such as the injector pressure plate, screw, injector rod and other accessories are not deformed, and install it in strict accordance with the operation steps of the engine maintenance manual.

A It is forbidden to operate the bare injector for a long time in an environment with serious dust $-\infty^{0.37}$ $\otimes^{\mathbb{N}_{2}}$ pollution and corrosion to iron products.

A It is forbidden to operate the bare injector for a long time in a strong magnetic field environment.

2.4. 32F61-00014 Injector Reasons of Not Working Normally There will a first a f

- (1) There is air in the oil circuit of the engine fuel system.
- (2) Vehicle oil pump oil supply system is not normal.
- (3) Engine common rail system oil leakage or pressure limiting valve damage.
- (4) There is a short circuit, cutting out and poor contact in the wiring harness connected to the fuel SPERF 336300 SPERM SPUTT States. SPARS
- injector of the vehicle.
- (5) The long-term placement of the injector causes the anti-rust oil to solidify, and the internal components are stuck or the oil holes are blocked.

A Before installing, carefully check whether other components in the common rail system except the fuel injector are damaged so as to prevent the fuel injector from not working properly after being replaced.

2.5. 32F61-00014 Injector Causes to Damage

- (1) Don't operate properly according to engine maintenance manual during dis-assembly or installation, resulting in damage to the injector.
- (2) The fuel oil used for the vehicle does not meet the standard cause damage to the injector, such as: the water content in the fuel oil exceeds the standard, iron powder, aluminum powder, sulfide impurities exceed the standard, etc.
- (3) The engine is not regularly maintained according to the engine maintenance manual (please refer to the vehicle maintenance manual for the maintenance mileage). For example, failure to replace the lubricating oil of the engine system for a long time will cause abnormal wear of the engine, excessive
- exhaust gas volume or a large amount of carbon deposits inside the engine. The filter is not replaced during maintenance or the replaced filter cannot reach the original filter standard. all above reasons -518-10⁷⁶ SPREAM can cause damage to the injector.
- (4) The abrasion of the oil pump produces iron powder and aluminum powder enter the fuel injector and STATE. cause damage to the fuel injector.
- (5) The deformation and abrasion of fuel tank result in iron powder or aluminum powder entering the fuel injector and causing damage to the fuel injector.
- (6) The fuel injector is damaged due to replacement or adjustment of the relevant parts of the fuel injector. For example, the valve clearance does not meet the standard after the engine is repaired, the replacement or modification of the wiring harness connected to the injector fails to meet the original standard.
- (7) The engine is overheated and overloaded for a long time working results in damage to the fuel injector. -SASTA
- (8) The injector will be damaged naturally at the end of its working life.
- (9) The injector is magnetized (injector parts' magnetic exceeded) causing the injector to not work properly.

Before replacing the fuel injector, please check the engine parts carefully according to the engine maintenance manual to avoid the fuel injector being damaged again after replacement. $\mathfrak{sl}^{[k]}$

2.6. 32F61-00014 Injector Technical Support Obtaining Methods

- (1) Injector Technical File, visit <u>http://shumatt.com</u> to get the technical file.
- (2) Injector Technical Videos

Facebook: Visit https://www.facebook.com/hison.li to get the technical videos, constantly follow can get more information.

YouTube: https://www.youtube.com/channel/UCByvYBx7VjV mAfxh Hu-aw to get the technical videos,

Mob/Whatsapp: +86 13410541523 Email :ruby@shumatt.com © 2023 Shenzhen Shumatt Technology Co., Ltd

constantly follow can get more information.

Shumatt: Visit http://shumatt.com to get the technical videos.

(3) Injector Information Query Software

TruckBook Parts EPC APP, Android/Apple App Store download and install, visit http://shumatt.com to get SPEER -SALER the download and installation tutorial.

(4) Search The fuel injector test data through TruckBook Parts EPC APP.

3. 32F61-00014 Injector Purchase and Delivery

3.1.32F61-00014 Injector Purchase Payment Term

Payment Terms: T/T, PayPal, Alipay, WeChat

Please contact our salesmen for specific payment information.

3.2. 32F61-00014 Injector Main Sales Markets

Injector main sales markets: Asia, Europe, North America, South America, Africa etc.

3.3. 32F61-00014 Injector Declaration Requirements

AUDIT Shumatt can assist customers to provide the following documents for import customs clearance: contract, invoice, packing list, bill of lading, insurance policy, certificate of origin, etc.

SHIP

- All States

3.4. 32F61-00014 Injector Shipping Ways

Destination in China areas: SF Express, Debon Express, the corresponding logistics company can be provided according to customer requirements in special cases.

Destinations out of China's areas: DHL, UPS, FedEx, TNT air, ocean or other shipping methods required by customers.

3.5. 326-4700 Injector Lead time

Lead time: Send out within 3 – 7 working days after receiving payment (Except for special products and special cases).

3.6.32F61-00014 Injector Logistics Time for Destination Out of China's Areas

DHL Logistics Time:	an a	22	\$1,000 C	31. J.	Store.	24	. 3hr.	Store.	Stor.	250
Country or Region of Departure	Hong Kong, China		Countries or ons of Asia	Au	stralia and N Zealand	lew	Europe	America	Other Countries	
China's Mainland	7 Days	S.	7 Days	a san	8 Days	1	8 Days	8-12 Days	7-10 Days	$z_{i}^{(0)}$

UPS Logistics Time: Country or Region of Departure: China's Mainland

Country of Destination	Estimated Arrival Time	Country of Destination	Estimated Arrival Time	Country of Destination	Estimated Arrival Time
Japan	3 Days	UK	5-7Days	Egypt	5-7 Days
Turkey	5-7 Days	Singapore	3 Days	Switzerland	5-7 Days
Bahrain	5-7 Days	Latvia	7-10 Days	New Zealand	7-10 Days
Sri Lanka	5-7 Days	Thailand	3 Days	Austria	5-7 Days
Romania	5-7 Days	Vietnam	3-5 Days	Estonia	5-7 Days
Malaysia	3-5 Days	Israel	5-7 Days	Mexico	7-10 Days

Mob/Whatsapp: +86 13410541523 Email :ruby@shumatt.com © 2023 Shenzhen Shumatt Technology Co., Ltd

France	5-7 Days	America	5-7 Days	United Arab Emirates	5-7 Days	
Italy	5-7 Days	Netherlands	5-7 Days	Bengat	7-10 Days	
Lebanon	5-7 Days	Philippine	3-5 Days	Greece	7-10 Days	241
South Korea	3 Days	Spain	5-7 Days	Myanmar	5-7 Days	
Canada	5-7 Days	Germany	5-7 Days	Saudi Arabia	7-10 Days	р ^{р.}
Portugal	5-7 Days	Australia	5-7 Days	South Africa	7-10 Days	
Denmark	5-7 Days	Belgium	5-7 Days	Ukraine	7-10 Days	g§
India	7-10 Days	Qatar	7-10 Days	Poland	5-7 Days	
Indonesia	3-5 Days	Morocco	7-10 Days	Pakistan	7-10 Days	de la
Kuwait	7-10 Days				200 A	

The logistics time is for reference only, subjects are according to the actual arrival.

3.7. 32F61-00014 Injector Packing

Domestic express packaging: Usually wrapped in waterproof scotch tape, such as picture No.2. **International express packaging:** Wrapped with waterproof yellow tape After wrapping the black protective film, such as picture No. 3.

Pallet Shipping: Use fumigation free and recycling trays that meet export requirements, and use white wrapping protective film to wrap and bind with cable ties for the outside, such as picture No. 4,also, the products can be packaged according to customers' requirements.

A The packing tray is made of plastic and can be recycled.

A Transparent tape, yellow tape, black wrapping protective film, white wrapping protective film are

non-degradable materials, please dispose of them properly.

Minors are prohibited from using transparent tape, yellow tape, black wrapping protective film, and white wrapping protective film to avoid personal injury.



Pic No. 2 Domestic express packaging: Wrapped by Transparent tape

International express packaging: Wrapped with yellow tape after wrapping black protective film

Mob/Whatsapp: +86 13410541523 Email :<u>ruby@shumatt.com</u> © 2023 Shenzhen Shumatt Technology Co., Ltd Tel: +8675523215133 Website : www.shumatt.com

10/15



Pic No. 4

Pallet Shipping: Use pallet that meet export requirements, and use white wrapping protective film to wrap and bind with cable ties

4. 32F61-00014 Injector Storage Standard

(1) Choose a suitable storage place

SHUMATT

The warehouse and cargo yard where the fuel injector is stored should be kept clean and dry, and away from the factory buildings that generate harmful gases and dust; do not mix with acid, alkali, salt and other substances; the storage place should have a good drainage system; the cargo yard should be flattened with gravel or furnace ash etc. to enhance the water permeability of the surface layer to keep the reservoir area and Car dry.

155

(2) Strict requirements of warehousing

Strict inspections should be carried out when the fuel injectors are put into storage, the surface cleaning work should be done well to remove water traces, oil stains, ash and other dirt, remove the rust and do anti-rust treatment in time. Packaged injectors must be protected from damage.

(3) Keep the warehouse dry and preventing moisture

The relative humidity is usually below 70% for the fuel injectors placed in the room, and the corrosion of the fuel injectors is significantly reduced.

Injectors must be stored in the warehouse, and they are forbidden to store in the same warehouse with commodities with high water content.

(4) Stack Properly

and and and a start a start . After the injector is exposed to rain, the corrosion rate will increase significantly. The purpose of sealing is to isolate the injector from rainwater and humid air, so the warehouse window should be checked in time to avoid rainwater entering the warehouse

If the fuel injector package is damaged, it should be repaired or replaced; when the package is damp, the packaging material should be dried; if the original anti-corrosion and oil applied at the factory is found to be damaged or dried up, it should be cleaned and re-applied oil in time.

It is forbidden to leave the injector exposed in the air for a long time.

It is forbidden to store acid, alkali, salt and other substances together with the injector.

A The unpacked fuel injector must be rust-proof during secondary storage.

5. Company Information when i share share



Telephone: +86-755-23215133

Email: ruby@shumatt.com

Website: www.shumatt.net

Shenzhen Office: 11-12, Floor 14, Building 13, Qinchengda Building, Exit A, Honglang North Subway Station, Bao'an District, Shenzhen, China's Mainland

SPORT

Shenzhen Office: Room 428-430, Building B, Huafeng Zhigu Technology Industrial Park, Exit B, Fuyong Metro Station, Bao'an District, Shenzhen, China's Mainland

THE THE THE ATT A THE ATT AND A THE ATT AND A THE ATT AND A THE ATT A

Hong Kong Office: Jianfa Street Industrial Zone, Tuen Mun, New Territories, Hong Kong, China

58.⁵⁷⁸

Mob/Whatsapp: +86 13410541523 Email :<u>ruby@shumatt.com</u> © 2023 Shenzhen Shumatt Technology Co., Ltd • After-sales Service Address: Please contact our salesmen to obtain and provide the corresponding product maintenance reasons (Reference: <u>1.10.326-4700 Injector Warranty Instructions</u>)

5.2	. Contact Information	1	the set of the set	6	ST water				
No.	Name	WeChat/ WhatsApp	Email	Facebook	YouTube				
1	Ruby	+86-13410541523	ruby@shumatt.com	Hison Li	Hison Li				
2	lvy	+86-18025309821	sales@shumatt.com	Ivy Shumatt	Shumatt IVY				
3. ₃₀ 0	Rebecca	+86-18025349821	sales01@shumatt.com	Rebecca SHUMATT	SHUMATT Rebecca				
4	Janny	+86-18028749821	sales02@shumatt.com	Janny shumatt	Janny Shumatt				
5	Sam	+86-13316859821	Sales8@shumatt.com	Shumatt Sam	Sam Shumatt				
6	Natalie	+86- 18938945856	sales15@shumatt.com	Shumatt Natalie	Lin Natalie				
7300	Bhi Ada Bhi	+86-1342286353	sales5@shumatt.com	Shumatt Ada	Ada Shumatt				
8	Hison Li	+86-18318811871	web@shumatt.com	Hison Li	Hison Li				
9	Mecca	+86-18938948618	sales11@shumatt.com	Shumatt Mecca	Shumatt Mecca				
10	Peric 39	+86 18319033618	sales3@shumatt.com	All All	All de				
11	[™] Wayne [™] (Joaquín en español)	+86-13316959821	wayne@shumatt.com	shumattwayne	Wayne Shumatt				
12	Sylvia	+86 18312499884	sales6@shumatt.com	i sti	Star Sta				
de la constance	Visit http://shumatt.com to obtain the latest information of salesmen								
		PS: Shumatt's sales-men's e	mails are all end with @shumatt.com						

6. Copyright Statement

The copyright of any contents (including but not limited to parameters, data, text, charts, images, sounds or videos, etc.) provided in " 320D Injector 32F61-00014 Technical File" belong to Shenzhen Shumatt Technology Co., Ltd. Without the prior written permission of Shenzhen Shumatt Technology Co., Ltd., you are not allowed to modify any contents in "320D Injector 32F61-00014 Technical File" in any way. At the same time, any conditions to spread, re-post, display the contents of "320D Injector 32F61-00014 Technical File" in any way. At the same time, any conditions to spread, re-post, display the contents of "320D Injector 32F61-00014 Technical File" in any way. At the same time, any conditions to use " 320D Injector 32F61-00014 Technical File" will violate the "Copyright Law of the People's Republic of China" and other laws and regulations and the provisions of relevant international conventions.