C9 Injector 267-3360 Technical File

SKU: Z1BK1002673360



3126 INJECTOR



C9 Injector 267-3360 Technical File The state of the s

1. 267-3360 Injector Introduction
1.1. 267-3360 Injector Basic Information
1.2. 267-3360 Injector Common Part Number
1.4. 267-3360 Injector Parameter1
1.5. 267-3360 Injector Specifications and Dimensions1
1.6. 267-3360 Injector Quality Control2
1.7. 267-3360 Injector Customized Service
1.8. 267-3360 Injector Packing List and Package Size2
1.9. 267-3360 Injector Testing Standard and Certificate
1-10. 267-3360 Injector Warranty Instructions4
1.11. 267-3360 Injector Manufacturer
2. 267-3360 Injector Technical Support5
2. 267-3360 Injector Technical Support
2.2. 326-4700 Injector Application Scenarios5
2.3. 267-3360 Injector Installation6
2.4. 267-3360 Injector Reasons of Not Working Normally7
2.5. 267-3360 Injector Causes to Damage
2.6. 267-3360 Injector Technical Support Obtaining Methods8
3. 267-3360 Injector Purchase and Delivery8
3,1.267-3360 Injector Purchase Payment Term8
3.2. 267-3360 Injector Main Sales Markets8
3.3. 267-3360 Injector Declaration Requirements
3.4. 267-3360 Injector Shipping Ways8
3.5. 326-4700 Injector Lead time
3.6.267-3360 Injector Logistics Time for Destination Out of China's Areas8
3.7. 267-3360 Injector Packing
4. 267-3360 Injector Storage Standard10
5. Company Information11
5.1. Company Introduction11
5.2. Contact Information12
6. Copyright Statement
THE TOTAL STREET, STR



C9 Injector 267-3360 Technical File

1. 267-3360 Injector Introduction

1.1.267-3360 Injector Basic Information

Title	China made new injector 267-3360 fuel injector for C9 Engine	- 500
SKU 1	Z1BK1002673360	e55

1.2. 267-3360 Injector Common Part Number

(1) Injector Exchange Information

Injector Part Number	Re-manufactured Part Number	Replacement Number	OE Number
267-3360	The The The	17 mg 1/2 1720	Mary Mary Mary
2673360	d. d	on ston I ston st	

(2) 267-3360 Matching Information

Car model	Engine	Engine	Engine	Engine	Engine	Engine
GRADER	160M		et ee	. at		
CRAWLER LOADER	973C	er.	States.	37 ¹⁰⁰⁰⁰ 3	Agr _{ador.} Algr	2000
WHEELED EXCAVATOR	M330D		ri Latingri			
WHEELED BULLDOZER	814F II		a s			
WHEELED SELF-PROPELLED SCRAPER	627G	637G	SINTER	27 July 3		38. J.
ENGINE - INDUSTRIAL	C9		C. The Control of the		all the contract of the contra	OF THE WARD
FOREST PRODUCTS	521	522	532	541	551	552
EARTHWORK COMPACTOR	815F II	816F II	Supraga,	SUPPLIES.	Marian Str	277.00
EXCAVATOR	330D	330D FM	330D L	330D LN	330D MH	

1.3, 267-3360 Injector Part Number Common Writing

267-3360, 267 3360, 2673360

1.4. 267-3360 Injector Parameter Adaptation System: HEUI System

Injector Series: C9 Series

Injector Type: Electromagnetic Injector **Vehicle Configuration Information:**C9 Engines

1.5. 267-3360 Injector Specifications and Dimensions Injector Size: 35cm* 14cm *14cm =6860cm3 (L*W*H=V)

Injector Net Weight: 1.9kg Injector Gross Weight: 2kg

Injector Quality: China Made New

Mob/Whatsapp: +86 13410541523

Email:ruby@shumatt.com

© 2023 Shenzhen Shumatt Technology Co., Ltd

1 / 14

Tel: +8675523215133

Package Size: 38cm* 15cm *15cm = 8550cm³ Injector Type: Diesel Common Rail Injector

MOQ: 4 Pieces

1.6. 267-3360 Injector Quality Control

(1) Injector Testing

All injector spare parts are tested for electrical characteristics, accuracy, high temperature, low temperature, withstand voltage, leakage, durability, and various working conditions.

(2) Injector Assembling

And the quality control of the injector production and installation process, our company strictly follows the standard product installation data and product installation steps to install, such as injector stroke test, injector solenoid valve tightening torque, injector nozzle tightening torque.

(3) Injector Inspection

The factory inspection of the injector is undergone full inspection, random inspection, and batch inspection three inspections. Different brands of test benches are used to test the same fuel injector for a total of no less than three times for factory inspection, and the fuel injector installation testing environment are progressed in dust-free workshop.

1.7. 267-3360 Injector Customized Service

(1) Injector Customized Service: Meet the customized needs of OEM manufacturers for shell lettering, logo engraving, injector internal packaging, injector external packaging and labels customized, etc.



(2) Injector Customized Service Requirements:

The purchased of customized injector are not less than 10 pieces.

Customized injector packages no less than 1000 pieces.

NOTES CO. Customized products involve the need of specify logo, the OEM manufacturer needs to provide trademark authorization and the sample of logo image file.

Once the customized fuel injector is sold, it cannot be returned or exchanged if there is no quality problems.

1.8. 267-3360 Injector Packing List and Package Size

(1) Injector Spare Parts List

(=,,					
No.	1	2	3		
Image			Ourosion pro		
Name	Fuel Injector	O-Ring	Nozzle Protective Cover Cap		
Description Fuel injector part number 267-3360		Ensure to meet the standard of the	Protect nozzle holes from		

Mob/Whatsapp: +86 13410541523 Tel: +8675523215133

Email:ruby@shumatt.com

© 2023 Shenzhen Shumatt Technology Co., Ltd

		<u> </u>		
		sealing performance between the injector and the engine	being polluted and blocked	
No.	4	5	6	
Image	St. Phys. Ph			
Name	VCI Anti-rust Bag	Injector Packing Box	Nozzle Gasket	
Description Prevent fuel injector from rusting		Package for injector and injector accessories Used to ensure the tight cap er injector and the engineers.		
Shippy Ship	M. Philippe, Philippe, Philippe, 2147	May the Market Strategy	Walley Halling Halling H	

Minors are forbidden to use the fuel injector assembly, O-ring, gasket, nozzle protective cover, fuel injector house protective cover, solenoid valve protective cover, VCI anti-rust bag, and air bubble bag to avoid personal injury,

⚠ O-ring and gasket are disposable installation accessories, and need to be replaced for

⚠ The nozzle protective cover, the injector house protective cover, and the solenoid valve protective cover are recyclable accessories that can be reused.

VCI anti-rust bags and bubble bags are non-degradable materials, please dispose of them properly after using. . The state of the

A The injector and the installation parts should be coated with appropriate sealing oil during installation.

(2) Injector Box Size



No.	Name		Injector Package Size (cm)				
37 1	Injector Box	20,000	38cm* 15 cm *15 cm = 8550 cm ³	Shan	27,000		

1.9. 267-3360 Injector Testing Standard and Certificate

Mob/Whatsapp: +86 13410541523 Tel: +8675523215133

Email:ruby@shumatt.com

© 2023 Shenzhen Shumatt Technology Co., Ltd

We can provide the factory quality inspection test report of each injector to ensure that each injector delivered meets the engine performance indicators.



1.10. 267-3360 Injector Warranty Instructions

(1) Product Warranty Conditions and Instructions

It is necessary to provide pictures, videos, or test reports detected by the injector inspection equipment when the injector is abnormal during use as evidence to feed back to the salesman.

Abnormal conditions are properly explained such as: 1.Smoke, 2. Engine shake, 3. Difficulty starting the

engine, 4. Engine noise, 5. oil leakage etc.

(2) Injector Warranty Coverage

Within 15 days after customer receives the 267-3360 injector, if there is a performance failure and the product has no appearance damage, customer can choose to replace it or repair it;

If the 267-3360 injector has performance problems during the warranty period (6-12 months), and it is confirmed that it is product's problems after testing, you can contact our salesmen to replace the same model or a reworked product with the same performance for free;

If the injector house has obvious scratches, it can only be repaired and it will be returned as it is if the product is confirmed to be fault-free.

Tips: For products not covered by warranty, our company can provide paid maintenance services. For products after paid repaired, the same performance problem will have a free warranty period within 3 months from the date of repairing.

(3) Injector Out of Warranty Coverage

The warranty period has expired.

Injector failure caused by high temperature, high pressure, humidity, rain and snow, saline-alkali land, earthquake, and used in abnormal environment.

Customer disassembles or repairs the injector personally resulting in damage to the injector.

Injector damage caused by man-made reasons (throwing, strong magnetic field magnetization, set fire).

Mob/Whatsapp: +86 13410541523 Tel: +8675523215133

Email: ruby@shumatt.com

© 2023 Shenzhen Shumatt Technology Co., Ltd

Injector failure or injector damage caused by non-injector design, technology, manufacturing, quality and other issues.

Injector failure due to system pressure exceeding system approved pressure.

Injector failure caused by system voltage exceeding approved voltage.

Injector failure caused by impurities (water, lead, aluminum powder, iron powder, sulfide) in the system fuel exceeding the standard requirements.

Injector failure caused by not installing according to the tightening torque specified in the vehicle engine maintenance manual (the tightening torque is too large or too small).

Injector failure caused by not following the installation angle specified in the vehicle engine maintenance manual.

Injector failure caused by not following the cleaning requirements specified in the vehicle engine maintenance manual.

Injector failure caused by failure to replace consumable parts as specified in the vehicle engine maintenance manual.

Injector failure caused by not complying with the intake system fit clearance and exhaust system fit clearance requirements specified in the vehicle engine maintenance manual.

Failure to replace the consumable parts and the fitting clearance of the oil inlet system pipeline and the fuel injector connection in accordance with the fuel intake system specified in the vehicle engine maintenance manual.

1.11. 267-3360 Injector Manufacturer

Injector manufacturer: Shenzhen Shumatt Technology Co., Ltd

2. 267-3360 Injector Technical Support

2.1. 267-3360 Injector Part Number Location

1) E.g.: The injector part number see as follows



	No.	Name			
ÇÎ	T AT SHEET	brand, logo, part number, series number			
	B.	nozzle part number			

2.2. 326-4700 Injector Application Scenarios

Suitable Car Model: Caterpillar C7 Engines

Mob/Whatsapp: +86 13410541523 Tel: +8675523215133

Email:ruby@shumatt.com

© 2023 Shenzhen Shumatt Technology Co., Ltd




Image 1

2.3. 267-3360 Injector Installation

(1) 267-3360 Injector Installation Precautions:

The replacement of the fuel injector must strictly follow the electrical system, the approved pressure of the low-pressure fuel intake system, the approved pressure of the high-pressure fuel circuit system, and fuel system replacement consumables requirements (including the low-pressure fuel circuit system filter and the high-pressure fuel circuit) specified in the vehicle engine maintenance manual;

A Replacement of wearing parts of the fuel system, cleaning requirements for the connection between the fuel system and the injector, the fitting clearance of the fuel injector connection, the installation angle and tightening torque of the injector, the fitting clearance of the intake system, and the fitting clearance of the exhaust system to ensure the service life of the engine and the normal operation of the injector.

⚠ When installing the fuel injector on the engine, it is necessary to clean the engine block, cylinder head and other parts connected to the fuel injector, and ensure that there is no dust, carbon deposits, water, rust spots, etc.

A Before installing, check whether the fuel injector nozzle gasket has been replaced and installed on the fuel injector.

When installing the fuel injector, apply lubricant between the fuel injector, fuel nozzle sealing gasket and O-ring.

A Without replacing new gasket can lead to: deformation of the tight cap of nozzle, deformation of nozzle, deformation of nozzle orifice, oil leakage and air leakage, which will cause serious damage to the fuel injector and nozzle to break and cause damage to the engine.

When installing the injector on the engine, please carefully check the components related to the installation of the injector, such as the injector pressure plate, screw, injector rod and other accessories are

Mob/Whatsapp: +86 13410541523 Tel: +8675523215133

Email:ruby@shumatt.com

© 2023 Shenzhen Shumatt Technology Co., Ltd



not deformed, and install it in strict accordance with the operation steps of the engine maintenance manual.

📤 It is forbidden to operate the bare injector for a long time in an environment with serious dust pollution and corrosion to iron products.

It is forbidden to operate the bare injector for a long time in a strong magnetic field environment.

2.4. 267-3360 Injector Reasons of Not Working Normally

- (1) There is air in the oil circuit of the engine fuel system.
- (2) Vehicle oil pump oil supply system is not normal.
- (3) Engine common rail system oil leakage or pressure limiting valve damage.
- (4) There is a short circuit, cutting out and poor contact in the wiring harness connected to the fuel injector of the vehicle.
- (5) The long-term placement of the injector causes the anti-rust oil to solidify, and the internal components are stuck or the oil holes are blocked.

Before installing, carefully check whether other components in the common rail system except the fuel injector are damaged so as to prevent the fuel injector from not working properly after being replaced.

2.5. 267-3360 Injector Causes to Damage

- (1) Don't operate properly according to engine maintenance manual during dis-assembly or installation, resulting in damage to the injector.
- (2) The fuel oil used for the vehicle does not meet the standard cause damage to the injector, such as: the water content in the fuel oil exceeds the standard, iron powder, aluminum powder, sulfide impurities exceed the standard, etc.
- (3) The engine is not regularly maintained according to the engine maintenance manual (please refer to the vehicle maintenance manual for the maintenance mileage). For example, failure to replace the lubricating oil of the engine system for a long time will cause abnormal wear of the engine, excessive exhaust gas volume or a large amount of carbon deposits inside the engine. The filter is not replaced during maintenance or the replaced filter cannot reach the original filter standard. all above reasons can cause damage to the injector.
- (4) The abrasion of the oil pump produces iron powder and aluminum powder enter the fuel injector and cause damage to the fuel injector.
- (5) The deformation and abrasion of fuel tank result in iron powder or aluminum powder entering the fuel injector and causing damage to the fuel injector.
- (6) The fuel injector is damaged due to replacement or adjustment of the relevant parts of the fuel injector. For example, the valve clearance does not meet the standard after the engine is repaired, the replacement or modification of the wiring harness connected to the injector fails to meet the original standard.
- (7) The engine is overheated and overloaded for a long time working results in damage to the fuel injector.
- (8) The injector will be damaged naturally at the end of its working life.
- (9) The injector is magnetized (injector parts' magnetic exceeded) causing the injector to not work properly.

Before replacing the fuel injector, please check the engine parts carefully according to the engine maintenance manual to avoid the fuel injector being damaged again after replacement.

Mob/Whatsapp: +86 13410541523 Tel: +8675523215133

Email:ruby@shumatt.com

© 2023 Shenzhen Shumatt Technology Co., Ltd



2.6. 267-3360 Injector Technical Support Obtaining Methods

- (1) Injector Technical File, visit http://shumatt.com to get the technical file.
- (2) Injector Technical Videos

Facebook: Visit https://www.facebook.com/hison.li to get the technical videos, constantly follow can get more information.

YouTube: https://www.youtube.com/channel/UCByvYBx7VjV mAfxh Hu-aw to get the technical videos, constantly follow can get more information.

Shumatt: Visit http://shumatt.com to get the technical videos.

(3) Injector Information Query Software

TruckBook Parts EPC APP, Android/Apple App Store download and install, visit http://shumatt.com to get the download and installation tutorial.

(4) Search The fuel injector test data through TruckBook Parts EPC APP.

3. 267-3360 Injector Purchase and Delivery

3.1,267-3360 Injector Purchase Payment Term

Payment Terms: T/T, PayPal, Alipay, WeChat

Please contact our salesmen for specific payment information.

3.2. 267-3360 Injector Main Sales Markets

Injector main sales markets: Asia, Europe, North America, South America, Africa etc.

3.3. 267-3360 Injector Declaration Requirements

Shumatt can assist customers to provide the following documents for import customs clearance: contract, invoice, packing list, bill of lading, insurance policy, certificate of origin, etc.

3.4. 267-3360 Injector Shipping Ways

Destination in China areas: SF Express, Debon Express, the corresponding logistics company can be provided according to customer requirements in special cases.

Destinations out of China's areas: DHL, UPS, FedEx, TNT air, ocean or other shipping methods required by customers.

3.5. 326-4700 Injector Lead time

Lead time: Send out within 3 – 7 working days after receiving payment (Except for special products and special cases).

3.6.267-3360 Injector Logistics Time for Destination Out of China's Areas

DHL Logistics Time:

Country or Region of Departure	Hong Kong, China	Other Countries or Regions of Asia	Australia and New Zealand	Europe	America	Other Countries
China's Mainland	7 Days	7 Days	8 Days	8 Days	8-12 Days	7-10 Days

UPS Logistics Time: Country or Region of Departure: China's Mainland

Country of Destination	Estimated Arrival Time	Country of Destination	Estimated Arrival Time	Country of Destination	Estimated Arrival Time
Japan	3 Days	UK	5-7Days	Egypt	5-7 Days
Turkey	5-7 Days	Singapore	3 Days	Switzerland	5-7 Days
Bahrain	5-7 Days	Latvia	7-10 Days	New Zealand	7-10 Days

Mob/Whatsapp: +86 13410541523 Tel: +8675523215133

Email:ruby@shumatt.com Website: www.shumatt.com

© 2023 Shenzhen Shumatt Technology Co., Ltd

Sri Lanka	5-7 Days	Thailand	3 Days	Austria	5-7 Days	
Romania	5-7 Days	Vietnam	3-5 Days	Estonia	5-7 Days	J. J. S. L.
Malaysia	3-5 Days	Israel	5-7 Days	Mexico	7-10 Days	p//
France	5-7 Days	America	5-7 Days	United Arab Emirates	5-7 Days	
Italy	5-7 Days	Netherlands	5-7 Days	Bengal	7-10 Days	95-
Lebanon	5-7 Days	Philippine	3-5 Days	Greece	7-10 Days	
South Korea	3 Days	Spain	5-7 Days	Myanmar	5-7 Days	98
Canada	5-7 Days	Germany	5-7 Days	Saudi Arabia	7-10 Days	
Portugal	5-7 Days	Australia	5-7 Days	South Africa	7-10 Days	180
Denmark	5-7 Days	Belgium	5-7 Days	Ukraine	7-10 Days	
India	7-10 Days	Qatar	7-10 Days	Poland	5-7 Days	. 6.
Indonesia	3-5 Days	Morocco	7-10 Days	Pakistan	7-10 Days	300
Kuwait	7-10 Days	The The T	Mar Mar	Titles Titles	Mary Mary	

The logistics time is for reference only, subjects are according to the actual arrival.

3.7. **267-3360** Injector Packing

Domestic express packaging: Usually wrapped in waterproof scotch tape, such as picture No.2.

International express packaging: Wrapped with waterproof yellow tape After wrapping the black protective film, such as picture No. 3.

Pallet Shipping: Use fumigation free and recycling trays that meet export requirements, and use white wrapping protective film to wrap and bind with cable ties for the outside, such as picture No. 4, also, the products can be packaged according to customers' requirements.



The packing tray is made of plastic and can be recycled.

A Transparent tape, yellow tape, black wrapping protective film, white wrapping protective film are non-degradable materials, please dispose of them properly.

 $oldsymbol{\mathbb{A}}$ Minors are prohibited from using transparent tape, yellow tape, black wrapping protective film, and white wrapping protective film to avoid personal injury.



Pic No. 2 Domestic express packaging: Wrapped by Transparent tape



Pic No. 3 International express packaging: Wrapped with yellow tape after wrapping black protective film

Mob/Whatsapp: +86 13410541523

Email:ruby@shumatt.com

© 2023 Shenzhen Shumatt Technology Co., Ltd

Tel: +8675523215133

100





Pic No. 4

Pallet Shipping: Use pallet that meet export requirements, and use white wrapping protective film to wrap and bind with cable ties

4. 267-3360 Injector Storage Standard

(1) Choose a suitable storage place

The warehouse and cargo yard where the fuel injector is stored should be kept clean and dry, and away from the factory buildings that generate harmful gases and dust; do not mix with acid, alkali, salt and other substances; the storage place should have a good drainage system; the cargo yard should be flattened with gravel or furnace ash etc. to enhance the water permeability of the surface layer to keep the reservoir area

(2) Strict requirements of warehousing

Strict inspections should be carried out when the fuel injectors are put into storage, the surface cleaning work should be done well to remove water traces, oil stains, ash and other dirt, remove the rust and do anti-rust treatment in time. Packaged injectors must be protected from damage.

(3) Keep the warehouse dry and preventing moisture

The relative humidity is usually below 70% for the fuel injectors placed in the room, and the corrosion of the fuel injectors is significantly reduced.

Injectors must be stored in the warehouse, and they are forbidden to store in the same warehouse with commodities with high water content.

CENT COUNTY OF THE COUNTY OF THE

(4) Stack Properly

After the injector is exposed to rain, the corrosion rate will increase significantly. The purpose of sealing is to isolate the injector from rainwater and humid air, so the warehouse window should be checked in time to avoid rainwater entering the warehouse

If the fuel injector package is damaged, it should be repaired or replaced; when the package is damp, the packaging material should be dried; if the original anti-corrosion and oil applied at the factory is found to be damaged or dried up, it should be cleaned and re-applied oil in time.



⚠ It is forbidden to leave the injector exposed in the air for a long time.

Mob/Whatsapp: +86 13410541523 Tel: +8675523215133

Email:ruby@shumatt.com Website: www.shumatt.com

© 2023 Shenzhen Shumatt Technology Co., Ltd

It is forbidden to store acid, alkali, salt and other substances together with the injector.

The unpacked fuel injector must be rust-proof during secondary storage.

5. Company Information



5.1. Company Introduction

Chinese Name: 深圳市舒马特科技有限公司

English Name: Shenzhen Shumatt Technology Co., Ltd

Mob Phone/WeChat: +86-13410541523

HK Telephone: +852-67653519

Telephone: +86-755-23215133

Email: ruby@shumatt.com

Website: www.shumatt.net

Shenzhen Office: 11-12, Floor 14, Building 13, Qinchengda Building, Exit A, Honglang North Subway Station, Bao'an District, Shenzhen, China's Mainland

Shenzhen Office: Room 428-430, Building B, Huafeng Zhigu Technology Industrial Park, Exit B, Fuyong Metro Station, Bao'an District, Shenzhen, China's Mainland

THE THE PERSON THE THE THE PERSON THE THE THE PERSON THE THE THE THE THE

Hong Kong Office: Jianfa Street Industrial Zone, Tuen Mun, New Territories, Hong Kong, China

Mob/Whatsapp: +86 13410541523

Email:ruby@shumatt.com

© 2023 Shenzhen Shumatt Technology Co., Ltd

Tel: +8675523215133



After-sales Service Address: Please contact our salesmen to obtain and provide the corresponding product maintenance reasons (Reference: 1.10. 326-4700 Injector Warranty Instructions

5.2. Contact Information

No.	Name	WeChat/ WhatsApp	Email	Facebook	YouTube
1	Ruby	+86-13410541523	ruby@shumatt.com	Hison Li	Hison Li
2	lvy	+86-18025309821	sales@shumatt.com	Ivy Shumatt	Shumatt IVY
3. ₅₇ /\.	Rebecca	+86-18025349821	sales01@shumatt.com	Rebecca SHUMATT	SHUMATT Rebecca
4	Janny	+86-18028749821	sales02@shumatt.com	Janny shumatt	Janny Shumatt
5	Sam	+86-13316859821	Sales8@shumatt.com	Shumatt Sam	Sam Shumatt
6	Natalie	+86- 18938945856	sales15@shumatt.com	Shumatt Natalie	Lin Natalie
730	301 Ada 301	+86-1342286353	sales5@shumatt.com	Shumatt Ada	Ada Shumatt
8	Hison Li	+86-18318811871	web@shumatt.com	Hison Li	Hison Li
9	Mecca	+86-18938948618	sales11@shumatt.com	Shumatt Mecca	Shumatt Mecca
10	Eric	+86 18319033618	sales3@shumatt.com	200 m	
11	Wayne (Joaquín en español)	+86-13316959821	wayne@shumatt.com	shumattwayne	Wayne Shumatt
12	Sylvia	+86 18312499884	sales6@shumatt.com		all water
600	An Thin Thin	Visit http://shumatt.com to ob	otain the latest information of salesmo	en gjilija gjilija	500
	2	PS: Shumatt's sales-men's e	mails are all end with @shumatt.com	1	

6. Copyright Statement

The copyright of any contents (including but not limited to parameters, data, text, charts, images, sounds or videos, etc.) provided in "C9 Injector 267-3360 Technical File" belong to Shenzhen Shumatt Technology Co., Ltd. Without the prior written permission of Shenzhen Shumatt Technology Co., Ltd., you are not allowed to modify any contents in "C9 Injector 267-3360 Technical File" in any way. At the same time, any conditions to spread, re-post, display the contents of "C9 Injector 267-3360 Technical File" should indicate that the cited article is from Shenzhen Shumatt Technology Co., Ltd., Any actions failure to follow above conditions to use "C9 Injector 267-3360 Technical File" will violate the "Copyright Law of the People's Republic of China" and other laws and regulations and the provisions of relevant international conventions.

Mob/Whatsapp: +86 13410541523 Tel: +8675523215133

Email:ruby@shumatt.com Website: www.shumatt.com

© 2023 Shenzhen Shumatt Technology Co., Ltd