C9 Injector 293-4072 Technical File

SKU: K30000C92934072



3126 INJECTOR



# C9 Injector 293-4072 Technical File

# Takent Content of Land American

1. 293-4072 Injector Introduction					
1.1. 293-4072 Injector Basic Information	( <sup>1</sup> )	57 St	200 Pages		
1.2. 293-4072 Injector Common Part Number					1
1.3. 293-4072 Injector Part Number Common Writing	astir <sup>est</sup> .	asi (Constitution)			
1.4. 293-4072 Injector Parameter	r 3u	30			1
1.5. 293-4072 Injector Specifications and Dimensions					
1.6. 293-4072 Injector Quality Control	S)	58	50	500	
1.7. 293-4072 Injector Customized Service					2
1.8. 293-4072 Injector Packing List and Package Size		4.10 <sup>267</sup>	(d)	J. 1995	
1.9. 293-4072 Injector Testing Standard and Certificate	1 301	357	300		4
1.10. 293-4072 Injector Warranty Instructions		أوتوبي	أَرْبُرُوبِي		44
1.11. 293-4072 Injector Manufacturer		300	130 °		
2. 293-4072 Injector Technical Support					5
2. 293-4072 Injector Technical Support		4.11.11.11.11.11.11.11.11.11.11.11.11.11	45	J. 1965	
2.2. 326-4700 Injector Application Scenarios			(20)		ε
2.3. 293-4072 Injector Installation					e
2.4. 293-4072 Injector Reasons of Not Working Normally	P. 188	ACO 150	985 1000 - 1000	36	7
2.5. 293-4072 Injector Causes to Damage					7
2.5. 293-4072 Injector Causes to Damage	ds		430 m		8
3. 293-4072 Injector Purchase and Delivery	. 30				8
3.1.293-4072 Injector Purchase Payment Term		أناتويي	گانتهید.	أثانويي.	8تاتىپى
3.2. 293-4072 Injector Main Sales Markets	P. 50	57	200	30° 50°	8
3.3. 293-4072 Injector Declaration Requirements					8
3.4. 293-4072 Injector Shipping Ways			γ.161 · · · · · · · · · · · · · · · · · ·	. 19 <sup>90.</sup>	
3.5. 326-4700 Injector Lead time					8
3.6.293-4072 Injector Logistics Time for Destination Out o					<u>.</u>
3.7. 293-4072 Injector Packing	100 m	25 St			9
4. 293-4072 Injector Storage Standard					10
5. Company Information	وير المتحافظي		(1) (1) (1) (1) (1) (1) (1) (1) (1) (1)		11
5.1. Company Introduction			1971	1971	11
5.2. Contact Information					12
6. Copyright Statement	g. 2)	50 St	20g		12
SATURE SATURE SATURE SATURE SATURE SATURE SATURE	Walter of	Nagara est	STEET ST	200 ST	100 SH

TATE OF THE PARTY OF THE PARTY



# C9 Injector 293-4072 Technical File

## 1. 293-4072 Injector Introduction

### 1.1. 293-4072 Injector Basic Information

Title	China made new injector 293-4072 fuel injector for C9 Engine
SKU 1	K30000C92934072

### 1.2. 293-4072 Injector Common Part Number

### (1) Injector Exchange Information

Injector Part Number	Re-manufactured Part Number	Replacement Number	OE Number
293-4072	The The	17 mg 1/2 1720	Mary Mary Mary
2934072	d. d. 1	on ston I ston st	

### (2) 293-4072 Matching Information

Car model	Engine	Engine	Engine	Engine
grader	140M	160M		1
Crawler loader	973C	1987 St. 200	-18 18 18 ST - 31	12
PETROLEUM PRODUCTS	ri C9			
WHEELED EXCAVATOR	M330D	1	. /	/
Wheeled bulldozer	814F II		SARAN PARANCE SA	1¢
Wheeled self-propelled scraper	627G	637D	637E	637G
ENGINE - INDUSTRIAL	C9	/		1
Forest products	2390	\$2391	521	522
Forest products	532	541	(1 	552
Earthwork compactor	815F II	816F II	<i></i>	1
EXCAVATOR	330D	330D FM	330D L ST	330D LN
LACAVATOR LACAVATOR	330D MH	336D.1	336D L	STATE L

### 1.3. 293-4072 Injector Part Number Common Writing

293-4072, 293 4072, 2934072

1.4. 293-4072 Injector Parameter
Adaptation System: HEUI System
Injector Series: C9 Series

Injector Type: Electromagnetic Injector
Vehicle Configuration Information:C9 Engines

1.5. 293-4072 Injector Specifications and Dimensions

Mob/Whatsapp: +86 13410541523 Tel: +8675523215133

Email :ruby@shumatt.com Website : www.shumatt.com

Injector Size: 35cm\* 14cm \*14cm =6860cm3 (L\*W\*H=V)

Injector Net Weight: 1.9kg Injector Gross Weight: 2kg

Injector Quality: China Made New

Package Size: 38cm\* 15cm \*15cm = 8550cm<sup>3</sup> Injector Type: Diesel Common Rail Injector

MOQ: 4 Pieces

### 1.6. 293-4072 Injector Quality Control

# (1) Injector Testing

All injector spare parts are tested for electrical characteristics, accuracy, high temperature, low temperature, withstand voltage, leakage, durability, and various working conditions.

### (2) Injector Assembling

And the quality control of the injector production and installation process, our company strictly follows the standard product installation data and product installation steps to install, such as injector stroke test, injector solenoid valve tightening torque, injector nozzle tightening torque.

### (3) Injector Inspection

The factory inspection of the injector is undergone full inspection, random inspection, and batch inspection three inspections. Different brands of test benches are used to test the same fuel injector for a total of no less than three times for factory inspection, and the fuel injector installation testing environment are progressed in dust-free workshop.

### 1.7. 293-4072 Injector Customized Service

(1) Injector Customized Service: Meet the customized needs of OEM manufacturers for shell lettering, logo engraving, injector internal packaging, injector external packaging and labels customized, etc.



### (2) Injector Customized Service Requirements:

The purchased of customized injector are not less than 10 pieces.

Customized injector packages no less than 1000 pieces.

Customized products involve the need of specify logo, the OEM manufacturer needs to provide trademark authorization and the sample of logo image file.

Once the customized fuel injector is sold, it cannot be returned or exchanged if there is no quality problems.

Mob/Whatsapp: +86 13410541523 Tel: +8675523215133

Email:ruby@shumatt.com Website: www.shumatt.com



### 1.8. 293-4072 Injector Packing List and Package Size

### (1) Injector Spare Parts List

No.	1	2	3
Image			Corresion Production of the Corresion Production Produc
Name	Fuel Injector	O-Ring	Nozzle Protective Cover Cap
Description	Fuel injector part number 293-4072	Ensure to meet the standard of the sealing performance between the injector and the engine	Protect nozzle holes from being polluted and blocked
No.	4	5	6
		_	
Image			
Image	VCI Anti-rust Bag	Injector Packing Box	Nozzle Gasket

Minors are forbidden to use the fuel injector assembly, O-ring, gasket, nozzle protective cover, fuel injector house protective cover, solenoid valve protective cover, VCI anti-rust bag, and air bubble bag to avoid personal injury.

O-ring and gasket are disposable installation accessories, and need to be replaced for re-installation.

⚠ The nozzle protective cover, the injector house protective cover, and the solenoid valve protective cover are recyclable accessories that can be reused.

▲ VCI anti-rust bags and bubble bags are non-degradable materials, please dispose of them properly after using.

▲ The injector and the installation parts should be coated with appropriate sealing oil during installation.

#### (2) Injector Box Size

Mob/Whatsapp: +86 13410541523 Tel: +8675523215133

Email:ruby@shumatt.com

© 2023 Shenzhen Shumatt Technology Co., Ltd





No.	Name	Injector Package Size (cm)				
1	Injector Box	38cm* 15 cm *15 cm = 8550 cm <sup>3</sup>				

### 1.9. 293-4072 Injector Testing Standard and Certificate

We can provide the factory quality inspection test report of each injector to ensure that each injector delivered meets the engine performance indicators.



### 1.10. 293-4072 Injector Warranty Instructions

## (1) Product Warranty Conditions and Instructions

It is necessary to provide pictures, videos, or test reports detected by the injector inspection equipment when the injector is abnormal during use as evidence to feed back to the salesman.

Abnormal conditions are properly explained such as: 1.Smoke, 2. Engine shake, 3. Difficulty starting the engine, 4. Engine noise, 5. oil leakage etc.

### (2) Injector Warranty Coverage

Within 15 days after customer receives the 293-4072 injector, if there is a performance failure and the product has no appearance damage, customer can choose to replace it or repair it;

Mob/Whatsapp: +86 13410541523

Email:ruby@shumatt.com

© 2023 Shenzhen Shumatt Technology Co., Ltd

Tel: +8675523215133



If the 293-4072 injector has performance problems during the warranty period (6-12 months), and it is confirmed that it is product's problems after testing, you can contact our salesmen to replace the same model or a reworked product with the same performance for free;

If the injector house has obvious scratches, it can only be repaired and it will be returned as it is if the product is confirmed to be fault-free.

A Tips: For products not covered by warranty, our company can provide paid maintenance services. For products after paid repaired, the same performance problem will have a free warranty period within 3 months from the date of repairing.

### (3) Injector Out of Warranty Coverage

The warranty period has expired.

Injector failure caused by high temperature, high pressure, humidity, rain and snow, saline-alkali land, earthquake, and used in abnormal environment.

Customer disassembles or repairs the injector personally resulting in damage to the injector.

Injector damage caused by man-made reasons (throwing, strong magnetic field magnetization, set fire).

Injector failure or injector damage caused by non-injector design, technology, manufacturing, quality and other issues.

Injector failure due to system pressure exceeding system approved pressure.

Injector failure caused by system voltage exceeding approved voltage.

Injector failure caused by impurities (water, lead, aluminum powder, iron powder, sulfide) in the system fuel exceeding the standard requirements.

Injector failure caused by not installing according to the tightening torque specified in the vehicle engine maintenance manual (the tightening torque is too large or too small).

Injector failure caused by not following the installation angle specified in the vehicle engine - Apply Apply Apply Apply Apply Apply

Injector failure caused by not following the cleaning requirements specified in the vehicle engine 

Injector failure caused by failure to replace consumable parts as specified in the vehicle engine 200 450

Injector failure caused by not complying with the intake system fit clearance and exhaust system fit clearance requirements specified in the vehicle engine maintenance manual.

Failure to replace the consumable parts and the fitting clearance of the oil inlet system pipeline and the fuel injector connection in accordance with the fuel intake system specified in the vehicle engine maintenance manual.

### 1.11. 293-4072 Injector Manufacturer

Injector manufacturer: Shenzhen Shumatt Technology Co., Ltd

### 2. 293-4072 Injector Technical Support

#### 2.1. 293-4072 Injector Part Number Location

1) E.g.: The injector part number see as follows

No.	Name	P
-----	------	---


Mob/Whatsapp: +86 13410541523 Tel: +8675523215133

Email:ruby@shumatt.com

© 2023 Shenzhen Shumatt Technology Co., Ltd

5 / 14

There There is the



or Ari	brand, logo, part number, series number
В	nozzle part number

### 2.2. 326-4700 Injector Application Scenarios

Suitable Car Model: Caterpillar C7 Engines




Image 1

# 2.3. 293-4072 Injector Installation

### (1) 293-4072 Injector Installation Precautions:

The replacement of the fuel injector must strictly follow the electrical system, the approved pressure of the low-pressure fuel intake system, the approved pressure of the high-pressure fuel circuit system, and fuel system replacement consumables requirements (including the low-pressure fuel circuit system filter and the high-pressure fuel circuit) specified in the vehicle engine maintenance manual;

A Replacement of wearing parts of the fuel system, cleaning requirements for the connection between the fuel system and the injector, the fitting clearance of the fuel injector connection, the installation angle and tightening torque of the injector, the fitting clearance of the intake system, and the fitting clearance of the exhaust system to ensure the service life of the engine and the normal operation of the injector.

⚠ When installing the fuel injector on the engine, it is necessary to clean the engine block, cylinder head and other parts connected to the fuel injector, and ensure that there is no dust, carbon deposits, water, rust spots, etc.

 $oldsymbol{oldsymbol{oldsymbol{eta}}}$  Before installing, check whether the fuel injector nozzle gasket has been replaced and installed on the

Mob/Whatsapp: +86 13410541523 Tel: +8675523215133

Email: ruby@shumatt.com

© 2023 Shenzhen Shumatt Technology Co., Ltd

6 / 14

fuel injector.

⚠ When installing the fuel injector, apply lubricant between the fuel injector, fuel nozzle sealing gasket and O-ring.

Without replacing new gasket can lead to: deformation of the tight cap of nozzle, deformation of nozzle, deformation of nozzle orifice, oil leakage and air leakage, which will cause serious damage to the fuel injector and nozzle to break and cause damage to the engine.

When installing the injector on the engine, please carefully check the components related to the installation of the injector, such as the injector pressure plate, screw, injector rod and other accessories are not deformed, and install it in strict accordance with the operation steps of the engine maintenance manual.

▲ It is forbidden to operate the bare injector for a long time in an environment with serious dust pollution and corrosion to iron products.

 $oldsymbol{\Lambda}$  It is forbidden to operate the bare injector for a long time in a strong magnetic field environment.

### 2.4. 293-4072 Injector Reasons of Not Working Normally

- (1) There is air in the oil circuit of the engine fuel system.
- (2) Vehicle oil pump oil supply system is not normal.
- (3) Engine common rail system oil leakage or pressure limiting valve damage.
- (4) There is a short circuit, cutting out and poor contact in the wiring harness connected to the fuel injector of the vehicle.
- (5) The long-term placement of the injector causes the anti-rust oil to solidify, and the internal components are stuck or the oil holes are blocked.

Before installing, carefully check whether other components in the common rail system except the fuel injector are damaged so as to prevent the fuel injector from not working properly after being replaced.

# 2.5. 293-4072 Injector Causes to Damage

- (1) Don't operate properly according to engine maintenance manual during dis-assembly or installation, resulting in damage to the injector.
- (2) The fuel oil used for the vehicle does not meet the standard cause damage to the injector, such as: the water content in the fuel oil exceeds the standard, iron powder, aluminum powder, sulfide impurities exceed the standard, etc.
- (3) The engine is not regularly maintained according to the engine maintenance manual (please refer to the vehicle maintenance manual for the maintenance mileage). For example, failure to replace the lubricating oil of the engine system for a long time will cause abnormal wear of the engine, excessive exhaust gas volume or a large amount of carbon deposits inside the engine. The filter is not replaced during maintenance or the replaced filter cannot reach the original filter standard. all above reasons can cause damage to the injector.
- (4) The abrasion of the oil pump produces iron powder and aluminum powder enter the fuel injector and cause damage to the fuel injector.
- (5) The deformation and abrasion of fuel tank result in iron powder or aluminum powder entering the fuel injector and causing damage to the fuel injector.

Mob/Whatsapp: +86 13410541523 Tel: +8675523215133

Email:ruby@shumatt.com Website: www.shumatt.com



- (6) The fuel injector is damaged due to replacement or adjustment of the relevant parts of the fuel injector. For example, the valve clearance does not meet the standard after the engine is repaired, the replacement or modification of the wiring harness connected to the injector fails to meet the original standard.
- (7) The engine is overheated and overloaded for a long time working results in damage to the fuel injector.
- (8) The injector will be damaged naturally at the end of its working life.
- (9) The injector is magnetized (injector parts' magnetic exceeded) causing the injector to not work properly.

Before replacing the fuel injector, please check the engine parts carefully according to the engine maintenance manual to avoid the fuel injector being damaged again after replacement.

### 2.6. 293-4072 Injector Technical Support Obtaining Methods

- (1) Injector Technical File, visit http://shumatt.com to get the technical file.
- (2) Injector Technical Videos

**Facebook:** Visit <a href="https://www.facebook.com/hison.li">https://www.facebook.com/hison.li</a> to get the technical videos, constantly follow can get more information.

**YouTube:** <a href="https://www.youtube.com/channel/UCByvYBx7VjV">https://www.youtube.com/channel/UCByvYBx7VjV</a> mAfxh Hu-aw to get the technical videos, constantly follow can get more information.

Shumatt: Visit http://shumatt.com to get the technical videos.

(3) Injector Information Query Software

TruckBook Parts EPC APP, Android/Apple App Store download and install, visit <a href="http://shumatt.com">http://shumatt.com</a> to get the download and installation tutorial.

(4) Search The fuel injector test data through TruckBook Parts EPC APP.

### 3. 293-4072 Injector Purchase and Delivery

### 3.1.293-4072 Injector Purchase Payment Term

**Payment Terms:** T/T, PayPal, Alipay, WeChat

Please contact our salesmen for specific payment information.

### 3.2. 293-4072 Injector Main Sales Markets

Injector main sales markets: Asia, Europe, North America, South America, Africa etc.

#### 3.3. 293-4072 Injector Declaration Requirements

Shumatt can assist customers to provide the following documents for import customs clearance: contract, invoice, packing list, bill of lading, insurance policy, certificate of origin, etc.

### 3.4. 293-4072 Injector Shipping Ways

**Destination in China areas:** SF Express, Debon Express, the corresponding logistics company can be provided according to customer requirements in special cases.

**Destinations out of China's areas:** DHL, UPS, FedEx, TNT air, ocean or other shipping methods required by customers.

### 3.5. 326-4700 Injector Lead time

**Lead time:** Send out within 3-7 working days after receiving payment (Except for special products and special cases).

Mob/Whatsapp: +86 13410541523 Tel: +8675523215133

Email:ruby@shumatt.com Website: www.shumatt.com



### 3.6.293-4072 Injector Logistics Time for Destination Out of China's Areas

DHL Logistics Time:

Country or Region of Departure	Hong Kong, China	Other Countries or Regions of Asia	Australia and New Zealand	Europe	America	Other Countries
China's Mainland	7 Days	7 Days	8 Days	8 Days	8-12 Days	7-10 Days

UPS Logistics Time: Country or Region of Departure: China's Mainland

Country of Destination	Estimated Arrival Time	Country of Destination	Estimated Arrival Time	Country of Destination	Estimated Arrival Time
Japan	3 Days	UK	5-7Days	Egypt	5-7 Days
Turkey	5-7 Days	Singapore	3 Days	Switzerland	5-7 Days
Bahrain	5-7 Days	Latvia	7-10 Days	New Zealand	7-10 Days
Sri Lanka	5-7 Days	Thailand	3 Days	Austria	5-7 Days
Romania	5-7 Days	Vietnam	3-5 Days	Estonia	5-7 Days
Malaysia	3-5 Days	Israel	5-7 Days	Mexico	7-10 Days
France	5-7 Days	America	5-7 Days	United Arab Emirates	5-7 Days
ltaly s	5-7 Days	Netherlands	5-7 Days	Bengal	7-10 Days
Lebanon	5-7 Days	Philippine	3-5 Days	Greece	7-10 Days
South Korea	3 Days	Spain	5-7 Days	Myanmar	5-7 Days
Canada	5-7 Days	Germany	5-7 Days	Saudi Arabia	7-10 Days
Portugal	5-7 Days	Australia	5-7 Days	South Africa	7-10 Days
Denmark	5-7 Days	Belgium	5-7 Days	Ukraine	7-10 Days
India	7-10 Days	Qatar	7-10 Days	Poland	5-7 Days
Indonesia	3-5 Days	Morocco	7-10 Days	Pakistan	7-10 Days
Kuwait	7-10 Days	a sa sa	200 200	25 25	201 201

The logistics time is for reference only, subjects are according to the actual arrival.

### 3.7. **293-4072** Injector Packing

**Domestic express packaging:** Usually wrapped in waterproof scotch tape, such as picture No.2.

International express packaging: Wrapped with waterproof yellow tape After wrapping the black protective film, such as picture No. 3.

Proc Pro

Pallet Shipping: Use fumigation free and recycling trays that meet export requirements, and use white wrapping protective film to wrap and bind with cable ties for the outside, such as picture No. 4, also, the products can be packaged according to customers' requirements.



The packing tray is made of plastic and can be recycled.

A Transparent tape, yellow tape, black wrapping protective film, white wrapping protective film are non-degradable materials, please dispose of them properly.

A Minors are prohibited from using transparent tape, yellow tape, black wrapping protective film, and white wrapping protective film to avoid personal injury.

Mob/Whatsapp: +86 13410541523

Email:ruby@shumatt.com







Pic No. 2

Domestic express packaging:
Wrapped by Transparent tape

Pic No. 3
International express packaging:
Wrapped with yellow tape after wrapping
black protective film



Pic No. 4

Pallet Shipping: Use pallet that meet export requirements, and use white wrapping protective film to wrap and bind with cable ties

### 4. 293-4072 Injector Storage Standard

### (1) Choose a suitable storage place

The warehouse and cargo yard where the fuel injector is stored should be kept clean and dry, and away from the factory buildings that generate harmful gases and dust; do not mix with acid, alkali, salt and other substances; the storage place should have a good drainage system; the cargo yard should be flattened with gravel or furnace ash etc. to enhance the water permeability of the surface layer to keep the reservoir area dry.

### (2) Strict requirements of warehousing

Strict inspections should be carried out when the fuel injectors are put into storage, the surface cleaning work should be done well to remove water traces, oil stains, ash and other dirt, remove the rust and do anti-rust treatment in time. Packaged injectors must be protected from damage.

### (3) Keep the warehouse dry and preventing moisture

The relative humidity is usually below 70% for the fuel injectors placed in the room, and the corrosion

Mob/Whatsapp: +86 13410541523

Email: ruby@shumatt.com

© 2023 Shenzhen Shumatt Technology Co., Ltd

Tel: +8675523215133

of the fuel injectors is significantly reduced.

Injectors must be stored in the warehouse, and they are forbidden to store in the same warehouse with commodities with high water content.

### (4) Stack Properly

After the injector is exposed to rain, the corrosion rate will increase significantly. The purpose of sealing is to isolate the injector from rainwater and humid air, so the warehouse window should be checked in time to avoid rainwater entering the warehouse

If the fuel injector package is damaged, it should be repaired or replaced; when the package is damp, the packaging material should be dried; if the original anti-corrosion and oil applied at the factory is found to be damaged or dried up, it should be cleaned and re-applied oil in time.

It is forbidden to leave the injector exposed in the air for a long time.

Shipping Shipping It is forbidden to store acid, alkali, salt and other substances together with the injector.

The unpacked fuel injector must be rust-proof during secondary storage.

# 5. Company Information



### 5.1. Company Introduction

Chinese Name: 深圳市舒马特科技有限公司

English Name: Shenzhen Shumatt Technology Co., Ltd

THE THE STREET

☐ Mob Phone/WeChat: +86-13410541523

HK Telephone: +852-67653519

Telephone: +86-755-23215133

Mob/Whatsapp: +86 13410541523

Email:ruby@shumatt.com

© 2023 Shenzhen Shumatt Technology Co., Ltd

Tel: +8675523215133



Email: ruby@shumatt.com

Website: www.shumatt.net

Shenzhen Office: 11-12, Floor 14, Building 13, Qinchengda Building, Exit A, Honglang North Subway Station, Bao'an District, Shenzhen, China's Mainland

Shenzhen Office: Room 428-430, Building B, Huafeng Zhigu Technology Industrial Park, Exit B, Fuyong Metro Station, Bao'an District, Shenzhen, China's Mainland

Hong Kong Office: Jianfa Street Industrial Zone, Tuen Mun, New Territories, Hong Kong, China

After-sales Service Address: Please contact our salesmen to obtain and provide the corresponding product maintenance reasons (Reference: 1.10. 326-4700 Injector Warranty Instructions

### 5.2. Contact Information

No.	Name	WeChat/ WhatsApp	Email	Facebook	YouTube		
1	Ruby	+86-13410541523	ruby@shumatt.com	Hison Li	Hison Li		
2	lvy	+86-18025309821	sales@shumatt.com	Ivy Shumatt	Shumatt IVY		
3	Rebecca	+86-18025349821	sales01@shumatt.com	Rebecca SHUMATT	SHUMATT Rebecca		
4	Janny Tanny	+86-18028749821	sales02@shumatt.com	Janny shumatt	Janny Shumatt		
5	Sam	+86-13316859821	Sales8@shumatt.com	Shumatt Sam	Sam Shumatt		
6	Natalie	+86- 18938945856	sales15@shumatt.com	Shumatt Natalie	Lin Natalie		
7 <sub>-00</sub> 0.	Ada	+86-1342286353	sales5@shumatt.com	Shumatt Ada	Ada Shumatt		
8	Hison Li	+86-18318811871	web@shumatt.com	Hison Li	Hison Li		
9	Mecca	+86-18938948618	sales11@shumatt.com	Shumatt Mecca	Shumatt Mecca		
10	Eric	+86 18319033618	sales3@shumatt.com	C			
11	Wayne ( Joaquín en español )	+86-13316959821	wayne@shumatt.com	shumattwayne	Wayne Shumatt		
12	Sylvia	+86 18312499884	sales6@shumatt.com	and the same	.ee.		
pt.	Visit http://shumatt.com to obtain the latest information of salesmen						
-911	PS: Shumatt's sales-men's emails are all end with @shumatt.com						

### 6. Copyright Statement

The copyright of any contents (including but not limited to parameters, data, text, charts, images, sounds or videos, etc.) provided in "C9 Injector 293-4072 Technical File" belong to Shenzhen Shumatt Technology Co., Ltd. Without the prior written permission of Shenzhen Shumatt Technology Co., Ltd., you are not allowed to modify any contents in "C9 Injector 293-4072 Technical File" in any way. At the same time, any conditions to spread, re-post, display the contents of "C9 Injector 293-4072 Technical File" should indicate that the cited article is from Shenzhen Shumatt Technology Co., Ltd., Any actions failure to follow above conditions to use "C9 Injector 293-4072 Technical File" will violate the "Copyright Law of the People's Republic of China" and other laws and regulations and the provisions of relevant international conventions.

Mob/Whatsapp: +86 13410541523 Tel: +8675523215133

Email:ruby@shumatt.com

© 2023 Shenzhen Shumatt Technology Co., Ltd