

AP63813BN Injector MTU Series Technical File

SKU: Z1K30AP63813BN



SHUMAT

AIME

SHUMAT

SHIMAT

AP63813BN Injector MTU Series Technical File

UMATT

SHUMAT

1 mri

IMIT

SHUMAT

Content

1	Content	A
SHJMM'	1. AP63813BN Injector Introduction	umri'
21	1.1. AP63813BN Injector Basic Information2	
1	1.2. AP63813BN Injector Common Part Number2	1
- Almin'	1.3. AP63813BN Injector Parameter2	unn'
31.	1.4. AP63813BN Injector Specifications and Dimensions2	
	1.5. AP63813BN Injector Quality Control2	
A IMAT	1.6. AP63813BN Injector Customized Service	UMAT
She	1.7. AP63813BN Injector Packing List and Package Size	
	1.8. AP63813BN Injector Testing Standard and Certificate5	
mint	1.9. AP63813BN Injector Warranty Instructions	min
SHUM	1.10. AP63813BN Injector Manufacturer	Cu.
	2. AP63813BN Injector Technical Support6	
T	2.1. AP63813BN Injector Part Number Location6	1
SHUMM	2.2. AP63813BN Injector Installation7	Ullin .
	2.3. AP63813BN Injector Reasons for Not Working Normally7	
	2.4. AP63813BN Injector Causes of Being Damaged7	
shumn.	2.5. AP63813BN Injector Technical Support Obtaining Methods	nuu.
21	3. AP63813BN Injector Purchase and Delivery8	
	3.1. AP63813BN Injector Purchase Payment Term8	
	3.2. AP63813BN Injector Main Sales Markets	UMAI
31.	3.3. AP63813BN Injector Declaration Requirements	
	3.4. AP63813BN Injector Shipping Ways	
	3.5. AP63813BN Injector Lead time	INFIT
SHE	3.6. AP63813BN Injector Logistics Time for Destination Out of China's Areas	
	3.7. AP63813BN Injector Packing	
Inne	4. AP63813BN Injector Storage Standard	Inn
SHUM	5. Company Information	Un
	5.1. Company Introduction	
1	5.2. Salesmen's Contact Information	1
-HUMM.	6. Copyright Statement	Uun.

SHUMAT Mob/WhatsApp: +86 13410541523 Email: ruby@shumatt.com © 2024 Shenzhen Shumatt Technology Co., Ltd

1

Tel: +8675523215133 Website Website : www.shumatt.com

AJMAT

1.mm

17

NIMIT

1/14

AIMAT

AP63813BN Injector MTU Series Technical File

1. AP63813BN Injector Introduction

1.1. AP63813BN Injector Basic Information

1.1. AP63813BN Ir	jector Basic Information	INFITT INFITT
Title	Common Rail AP63813BN Injector MTU Series	Quality
SKU	Z1K30AP63813BN	Re-manufactured
A A		A A

1.2. AP63813BN Injector Common Part Number

(1) Injector Exchange Information

	Injector Part Number	Compatible Number	Compatible Number	OE Number	a Immiti
0	1" SI" SI"	31. 31.	31. 31. 31.	31. 31. 3	24
	AP63813BN	1830692C91	1830691C1	2593597C91	
	TT TT	TT TT T	TT TT	TI TI TI	TT

Injector Application Information (2)

a Imiri

SHIME

۲	Car Model	Engine	Engine	UMATT
13	FORD	DT530	HT530	31
7	AUMITIT TRUCK	MTUNT MTUNT	Navistar	AUMATT

(3) Injector Part Number Common Writing AP63813BN, 1830692C91,1830691C1,2593597C91

1.3. AP63813BN Injector Parameter

Adaptation System: Common Rail System Injector Series: MTU Series **Injector Type: Diesel Injector** Vehicle Information: MTU Engines

1.4. AP63813BN Injector Specifications and Dimensions

Injector Size: 34cm* 13cm *13cm =5746cm³ Injector Net Weight: 1.37kg Injector Gross Weight: 1.4kg Injector Quality:Re-manufactured Injector Package Size: 35 cm* 15cm *15 cm = 7875cm³ Injector Type: Diesel Injector **Injector MOQ: 4 Pieces**

1.5. AP63813BN Injector Quality Control

(1) Injector Testing

All injector spare parts are tested for electrical characteristics, accuracy, high temperature, low temperature, withstand voltage, leakage, durability, and various working conditions.

(2) Injector Assembling

Mob/WhatsApp: +86 13410541523 Email: ruby@shumatt.com

Tel: +8675523215133 Website : www.shumatt.com

For the quality control of the injector production and installation process, our company strictly follows the standard product installation data and product installation steps to install, such as injector stroke test, injector solenoid valve tightening torque, injector nozzle tightening torque.

(3) Injector Inspection

SHUMATT

The factory inspection of the injector is undergone full inspection, random inspection, and batch inspection three inspections. Different brands of test benches are used to test the same fuel injector for more than three times for factory inspection, and the fuel injector installation testing environment are progressed in dust-free workshop.

1.6. AP63813BN Injector Customized Service

- Injector's Customized Service Coverage: Meet the customized needs of OEM manufacturers for shell (1) lettering, logo engraving, injector internal packaging, injector external packaging and labels customized,
 - etc.



(2) Injector's Customized Service Requirements:

The quantity of customized injectors shall not be less than 10 pieces.

The quantity of customized injector packages shall not be less than 1000 pieces.

Customized products involve the need of specify logo, the OEM manufacturer needs to provide trademark authorization and the sample of logo image file.

Once the customized fuel injector is sold, it cannot be returned or exchanged if there is no quality problem.

1.7. AP63813BN Injector Packing List and Package Size

(1) Injector Spare Parts List

SHUMA

7	No.	1	2	3	1
	strum strum	shum all sh	Ulin a lin a lin		11
7	SHUMMIN				
7	Name	Fuel injector	Nozzle Protective Cover	VCI Anti-rust Bag	
7	Description	Fuel injector part number: AP63813BN	Protect nozzle holes from being polluted and blocked	Prevent fuel injector from rusting	

Mob/WhatsApp: +86 13410541523 Email: ruby@shumatt.com

Tel: +8675523215133 Website : www.shumatt.com

SHUMATT Shenzhen Shumatt Technology Co., Ltd 4 5 No. 6 Image Name Lining **Oil Absorbing Paper Injector Packing Box** Prevent the injector from being Place injector and injector Description To prevent oil leaks damaged by external forces accessories 172


▲ Minors are forbidden to use the fuel injector assembly, O-ring, nozzle protective cover, fuel injector house protective cover, fuel return cover, VCI anti-rust bag, and air bubble bag to avoid personal injury.

• O-ring and nozzle gasket are disposable installation accessories, and need to be replaced for re-installation.

A The nozzle protective cover, the injector house protective cover, and the fuel return cover are recyclable accessories that can be reused.

▲ VCI anti-rust bags and bubble bags are non-degradable materials, please dispose them properly after using.

▲ The injector and the installation parts should be coated with appropriate sealing oil during installation.



atumni

1. Min

ininiti

SHUMI



Mob/WhatsApp: +86 13410541523 Email: <u>ruby@shumatt.com</u> © 2024 Shenzhen Shumatt Technology Co., Ltd Tel: +8675523215133 Website : <u>www.shumatt.com</u>

1.8. AP63813BN Injector Testing Standard and Certificate

Shumatt can provide the factory quality inspection test report of each injector to ensure that each delivered injector meets the engine performance indicators.

BOTEN		测试	服告	4.05.2019	10:42:09
列伸企业:					
912:		激	t;		
9月:			8人:		
ic∩##E. Bi∄:		323	8单位:		
9 15 :		WF	⁹ 姓名:		
的理论证:					
3件名称:	ND HE DA				
U号·零件号:	6				
RhA:					
istang: (00000.0014	检测	結果		
COLONY: 1	時に応援的	448238	Fisher Offic	800×108	
LEAR TEST:	32		**	20.84114	~
Rade:	35		75.7	# ***** ¢	1
WARM.	3.6	147 3 216 5	0		
Mast	2115	218 5±14.4		<u>r</u>	~
TL:	28.4	34.K±8.5	c 2	·····	1
U.:	14.1	15,7±4.8	69		~
VE:	47	4.5±1.8	63		*
	s Jew Jes L				

1.9. AP63813BN Injector Warranty Instructions

(1) Product Warranty Conditions and Instructions

It is necessary to provide pictures, videos, or test reports detected by the injector inspection equipment when the injector is abnormal during use as evidence to feed back to the salesman. Abnormal conditions are properly explained such as: 1.Smoke, 2. Engine shake, 3. Difficulty starting the engine, 4. Engine noise, 5. oil leakage etc.

(2) Injector Warranty Coverage

Within 15 days after customer receives the AP63813BN injector, if there is a performance failure and the product has no appearance damage, customer can choose to replace it or repair it;

If the AP63813BN injector has performance problems during the warranty period (6-12 months), and it is confirmed that it is product's problems after testing, you can contact our salesmen to replace the same model or a reworked product with the same performance for free;

If the injector house has obvious scratches, it can only be repaired and it will be returned as it is if the product is confirmed to be fault-free.

Tips: For products not covered by warranty, our company can provide paid maintenance services. For products after paid repaired, the same performance problem will have a free warranty period within 3 months from the date of repairing.

(3) Injector Out of Warranty Coverage

- The warranty period has expired.
- Injector failure caused by high temperature, high pressure, humidity, rain and snow, saline-alkali land, earthquake, and used in abnormal environment.
- Customer disassembles or repairs the injector personally resulting in damage to the injector.

Mob/WhatsApp: +86 13410541523 Email: ruby@shumatt.com Tel: +8675523215133 Website : <u>www.shumatt.com</u>

- Injector damage caused by man-made reasons (throwing, strong magnetic field magnetization, set fire).
 Injector failure or injector damage caused by non-injector design, technology, manufacturing, quality, and other issues.
- Injector failure due to system pressure exceeding system approved pressure.
- Injector failure caused by system voltage exceeding approved voltage.
- Injector failure caused by impurities (water, lead, aluminum powder, iron powder, sulfide) in the system fuel exceeding the standard requirements.
- Injector failure caused by not installing according to the tightening torque specified in the vehicle engine maintenance manual (the tightening torque is too large or too small).
- Injector failure caused by not following the installation angle specified in the vehicle engine maintenance manual.
- Injector failure caused by not following the cleaning requirements specified in the vehicle engine maintenance manual.
- Injector failure caused by failure to replace consumable parts as specified in the vehicle engine maintenance manual.
- Injector failure caused by not complying with the intake system fit clearance and exhaust system fit clearance requirements specified in the vehicle engine maintenance manual.
- Failure to replace the consumable parts and the fitting clearance of the oil inlet system pipeline and the fuel injector connection in accordance with the fuel intake system specified in the vehicle engine maintenance manual.

1.10. AP63813BN Injector Manufacturer

SHUMATT

Injector's Manufacturer: Shenzhen Shumatt Technology Co., Ltd

2. AP63813BN Injector Technical Support

2.1. AP63813BN Injector Part Number Location

1) E.g.: See the injector part number as follows



Mob/WhatsApp: +86 13410541523 Email: <u>ruby@shumatt.com</u> © 2024 Shenzhen Shumatt Technology Co., Ltd

Tel: +8675523215133 Website : <u>www.shumatt.com</u>

att reenhology co., Eta

2.2. AP63813BN Injector Installation

(1) AP63813BN Injector Installation Precautions:

▲ The replacement of the injector must strictly follow the electrical system, the approved pressure of the low-pressure fuel intake system, the approved pressure of the high-pressure fuel circuit system, and fuel system replacement consumables requirements (including the low-pressure fuel circuit system filter and the high-pressure fuel circuit) specified in the vehicle engine maintenance manual.

▲ Strictly follow the operation manual of replacement of wearing parts of the fuel system, cleaning requirements for the connection between the fuel system and the injector, the fitting clearance of the injector connection, the installation angle and tightening torque of the injector, the fitting clearance of the intake system, and the fitting clearance of the exhaust system, so that to ensure the service life of the engine and the normal operation of the injector.

▲ When installing the injector on the engine, it is necessary to clean the engine block, cylinder head and other parts connected to the injector, and ensure that there is no dust, carbon deposits, water, rust spots, etc.

A Before installing, check whether the injector nozzle gasket has been replaced and installed on the injector.

A When installing the injector, apply lubricant between the injector, injector nozzle sealing gasket and O-ring.

▲ If new a gasket is not replaced, it can lead to: deformation of the tight cap of nozzle, deformation of nozzle, deformation of nozzle orifice, oil leakage and air leakage, which will cause serious damage to the injector and nozzle to break and cause damage to the engine.

▲ When installing the injector on the engine, please carefully check the components related to the installation of the injector to ensure they are not deformed, such as the injector pressure plate, screw, injector rod and other accessories, and install it in strict accordance with the operation steps of the engine maintenance manual.

▲ It is forbidden to operate the bare injector for a long time in an environment with serious dust pollution and corrosion to iron products.

It is forbidden to operate the bare injector for a long time in a strong magnetic field environment.

2.3. AP63813BN Injector Reasons for Not Working Normally

- (1) There is air in the oil circuit of the engine fuel system.
- (2) Vehicle injector fuel supply system is not normal.
- (3) Engine common rail system oil leakage or pressure limiting valve damage.
- (4) There is a short circuit, cutting out and poor contact in the wiring harness connected to the fuel injector of the vehicle.
- (5) The long-term placement of the injector causes the anti-rust oil to solidify, and the internal components are stuck or the oil holes are blocked.

Before installing, carefully check whether other components in the common rail system except the fuel injector are damaged to prevent the fuel injector from not working properly after being replaced.

2.4. AP63813BN Injector Causes of Being Damaged

- (1) Didn't operate properly according to engine maintenance manual during disassembly or installation, resulting in damage to the injector.
- (2) The fuel oil used for the vehicle does not meet the standard cause damage to the injector, such as: the water content in the fuel oil exceeds the standard, iron powder, aluminum powder, sulfide impurities

Mob/WhatsApp: +86 13410541523 Email: ruby@shumatt.com Tel: +8675523215133 Website : <u>www.shumatt.com</u>

exceed the standard, etc.

SHUMATT

- (3) The engine is not regularly maintained according to the engine maintenance manual (please refer to the vehicle maintenance manual for the maintenance mileage). For example, failure to replace the lubricating oil of the engine system for a long time will cause abnormal wear of the engine, excessive exhaust gas volume or a large amount of carbon deposits inside the engine. The filter is not replaced during maintenance or the replaced filter cannot reach the original filter standard. all above reasons can cause damage to the injector.
- (4) The abrasion of the oil pump produces iron powder and aluminum powder enter the fuel injector and cause damage to the fuel injector.
- (5) The deformation and abrasion of fuel tank result in iron powder or aluminum powder entering the fuel injector and causing damage to the fuel injector.
- (6) The fuel injector is damaged due to replacement or adjustment of the relevant parts of the fuel injector. For example, the valve clearance does not meet the standard after the engine is repaired, the replacement or modification of the wiring harness connected to the injector fails to meet the original standard.
- (7) The engine is overheated and overloaded for a long-time working result in damage to the fuel injector.
- (8) The injector will be damaged naturally at the end of its working life.
- (9) The injector is magnetized (injector parts' magnetic exceeded) causing the injector to not work properly.

A Before replacing the fuel injector, please check the engine parts carefully according to the engine maintenance manual to avoid the fuel injector being damaged again after replacement.

2.5. AP63813BN Injector Technical Support Obtaining Methods

- (1) Injector Technical File , visit <u>http://shumatt.com</u> to get the technical file.
- (2) Injector Technical Videos

Facebook : Visit <u>https://www.facebook.com/hison.li</u> to get the technical videos, constantly follow can get more information.

YouTube : <u>https://www.youtube.com/channel/UCByvYBx7VjV_mAfxh_Hu-aw</u> to get the technical videos, constantly follow can get more information.

Shumatt: Visit <u>http://shumatt.com</u> to get the technical videos.

(3) Injector Information Query Software

TruckBook Parts EPC APP, Android/Apple App Store download and install, visit <u>http://shumatt.com</u> to get the download and installation tutorial

(4) Search The fuel injector test data through TruckBook Parts EPC APP.

3. AP63813BN Injector Purchase and Delivery

3.1. AP63813BN Injector Purchase Payment Term

Payment Terms: T/T, PayPal, Alipay, WeChat

A Please contact our salesmen for specific payment information.

3.2. AP63813BN Injector Main Sales Markets

Injector main sales markets: Asia, Europe, North America, South America, Africa etc.

3.3. AP63813BN Injector Declaration Requirements

Shumatt can assist customers to provide the following documents for import customs clearance:

Mob/WhatsApp: +86 13410541523 Email: ruby@shumatt.com Tel: +8675523215133 Website : <u>www.shumatt.com</u>

nimin

AIMIN

contract, invoice, packing list, bill of lading, insurance policy, certificate of origin, etc.

3.4. AP63813BN Injector Shipping Ways

. a lan

a JUL

Destination in China Areas: SF Express, Debon Express, the corresponding logistics company can be provided according to customer requirements in special cases.

Destinations Out of China's Areas : DHL, UPS, FedEx, TNT air, ocean or other shipping methods required by customers.

3.5. AP63813BN Injector Lead time

Lead time: Send out within 3 – 7 working days after receiving payment (Except for special products and special cases)

3.6. AP63813BN Injector Logistics Time for Destination Out of China's Areas

DHL Logistics Time :

Country or Region of Departure	Hong Kong, China	Other Countries or Regions of Asia	Australia and New Zealand	Europe	America	Other Countries
China's Mainland	7 Days	7 Days	8 Days	8 Days	8-12 Days	7-10 Days
				A Jun		

UPS Logistics Time: Country or Region of Departure: China's Mainland

Country of Destination	Estimated Arrival Time	Country of Destination	Estimated Arrival Time	Country of Destination	Estimated Arrival Time
Japan	3 Days	SHUM UKUM SH	5-7Days	Egypt	5-7 Days
Turkey	5-7 Days	Singapore	3 Days	Switzerland	5-7 Days
Bahrain	5-7 Days	Latvia	7-10 Days	New Zealand	7-10 Days
Sri Lanka	5-7 Days	Thailand	3 Days	Austria	5-7 Days
Romania	5-7 Days	Vietnam	3-5 Days	Estonia	5-7 Days
Malaysia	3-5 Days	Israel	5-7 Days	Mexico	7-10 Days
France	5-7 Days	America	5-7 Days	United Arab Emirates	5-7 Days
Italy	5-7 Days	Netherlands	5-7 Days	Bengal	7-10 Days
Lebanon	5-7 Days	Philippine	3-5 Days	Greece	7-10 Days
South Korea	3 Days	Spain	5-7 Days	Myanmar	5-7 Days
Canada	5-7 Days	Germany	5-7 Days	Saudi Arabia	7-10 Days
Portugal	5-7 Days	Australia	5-7 Days	South Africa	7-10 Days
Denmark	5-7 Days	Belgium	5-7 Days	Ukraine	7-10 Days
India	7-10 Days	Qatar	7-10 Days	Poland	5-7 Days
Indonesia	3-5 Days	Morocco	7-10 Days	Pakistan	7-10 Days
Kuwait	7-10 Days	stummer stummers	Mur. Shun	SHUMIT SHUMIT	SHUMIT'S SHU

A The logistics time is for reference only, subjects are according to the actual arrival.

3.7. AP63813BN Injector Packing

Domestic express packaging: Usually wrapped in waterproof scotch tape, such as picture No.2. **International express packaging :** Wrapped with waterproof yellow tape After wrapping the black protective film, such as picture No. 3.

Pallet Shipping: Use fumigation free and recycling trays that meet export requirements, and use white

Mob/WhatsApp: +86 13410541523 Email: ruby@shumatt.com Tel: +8675523215133 Website : <u>www.shumatt.com</u>

wrapping protective film to wrap and bind with cable ties for the outside, such as picture No. 4,

also, the products can be packaged according to customers' requirements.

The packing tray is made of plastic and can be recycled.

Transparent tape, yellow tape, black wrapping protective film, white wrapping protective film are n Imini non-degradable materials, please dispose of them properly.

Minors are prohibited from using transparent tape, yellow tape, black wrapping protective film, and white wrapping protective film to avoid personal injury. inuni



Pic No. 1 Domestic express packaging: Wrapped with Transparent tape

SHUMATT

SHUMA

SHUMA

ahumr

AUNIT

1 mir

1.mm

SHIMAT

AIMAI

SHIMF



SHUMA

anunti

AJMI




1 mř

AJMF

AIMÉ





Pallet Shipping: Use pallet that meet export requirements, and use white wrapping protective film to wrap and bind with cable ties

4. AP63813BN Injector Storage Standard

(1) Choose a suitable storage place

The warehouse and cargo yard where the fuel injector is stored should be kept clean and dry, and away from the factory buildings that generate harmful gases and dust; do not mix with acids, alkalis, salt and other substances; the storage place should have a good drainage system; the cargo yard should be flattened with gravel or furnace ash etc. to enhance the water permeability of the surface layer to keep the reservoir

Mob/WhatsApp: +86 13410541523 Email: ruby@shumatt.com

Tel: +8675523215133 Website : www.shumatt.com

© 2024 Shenzhen Shumatt Technology Co., Ltd

area dry.

(2) Strict requirements of warehousing

SHUMATT

Strict inspections should be carried out when the fuel injectors are put into storage, the surface cleaning work should be done well to remove water traces, oil stains, ash, and other dirt, remove the rust and do anti-rust treatment in time. Packaged injectors must be protected from damage.

(3) Keep the warehouse dry and preventing moisture

The relative humidity is usually below 70% for the fuel injectors placed in the room, and the corrosion of the fuel injectors is significantly reduced.

Injectors must be stored in the warehouse, and they are forbidden to store in the same warehouse with commodities with high water content.

(4) Stack Properly

After the injector is exposed to rain, the corrosion rate will increase significantly. The purpose of sealing is to isolate the injector from rainwater and humid air, so the warehouse window should be checked in time to avoid rainwater entering the warehouse

If the fuel injector package is damaged, it should be repaired or replaced; when the package is damp, the packaging material should be dried; if the original anti-corrosion and oil applied at the factory is found to be damaged or dried up, it should be cleaned and re-applied oil in time.

- It is forbidden to leave the injector exposed in the air for a long time.
- It is forbidden to store acids, alkalis, salt, and other substances together with the injector.
- A The unpacked fuel injector must be rust-proof during secondary storage.

5. Company Information

Office Locations

Global Exhibitions

Mob/WhatsApp: +86 13410541523 Email: <u>ruby@shumatt.com</u> © 2024 Shenzhen Shumatt Technology Co., Ltd Tel: +8675523215133 Website : <u>www.shumatt.com</u>

5.1. Company Introduction

Chinese Name: 深圳市舒马特科技有限公司 English Name: Shenzhen Shumatt Technology Co., Ltd

Mob Phone/WeChat: +86-13410541523

HK Telephone: +852-67653519

Telephone: +86-755-23215133

Email: ruby@shumatt.com

Website: www.shumatt.com

Shenzhen Office: 11-12, Floor 14, Building 13, Qinchengda Building, Exit A, Honglang North Subway Station, Bao'an District, Shenzhen, China's Mainland

Shenzhen Office : Exit C, Qiao Touxi Metro Station, NO. 66 Chongqing Road, Fuhai Avenue, Bao'an District, Shenzhen, China Mainland

♥ Hong Kong Office: Jianfa Street Industrial Zone, Tuen Mun, New Territories, Hong Kong, China

After-sales Service Address : Please contact our salesmen to obtain and provide the corresponding

product maintenance reasons (Reference: 1.9. AP63813BN Injector Warranty Instructions)

5.2. Salesmen's Contact Information

No.	Name	WeChat/WhatsApp	Email
5/1 5	Ruby	+86-13410541523	ruby@shumatt.com
2	lvy	+86-18025299821	sales@shumatt.com
31717	Rebecca	+86-18025349821	sales01@shumatt.com
314 3	Janny Shara	+86-18028749821	sales02@shumatt.com
5	Sam	+86-13316859821	Sales8@shumatt.com
6171	Natalie	+86- 18938945856	sales15@shumatt.com
317 3	Ada	+86-1342286353	sales5@shumatt.com
8	Hison Li	+86-18318811871	web@shumatt.com
9	Mecca	+86-18938948618	sales11@shumatt.com
10	Eric Share	+86 18319033618	sales3@shumatt.com
11	Wayne (Joaquín en español)	+86-13316959821	wayne@shumatt.com
51 12	Sylvia	+86 18312499884	sales6@shumatt.com
	Visit <u>http://shumatt</u>		on of salesmen
T MATT	PS: Shumatt's sal	esmen's emails are all end with @sl	humatt.com

Mob/WhatsApp: +86 13410541523 Email: <u>ruby@shumatt.com</u> © 2024 Shenzhen Shumatt Technology Co., Ltd Tel: +8675523215133 Website : <u>www.shumatt.com</u>

6. Copyright Statement

SHUMATT

The copyright of any contents (including but not limited to parameters, data, text, charts, images, sounds, or videos, etc.) provided in "AP63813BN Injector MTU Series Technical File" belong to Shenzhen Shumatt Technology Co., Ltd. Without the prior written permission of Shenzhen Shumatt Technology Co., Ltd., you are not allowed to modify any contents in "AP63813BN Injector MTU Series Technical File" in any way. At the same time, any conditions to spread, repost, display the contents of "AP63813BN Injector MTU Series Technical File" in any way. At the same time, any conditions to spread, repost, display the contents of "AP63813BN Injector MTU Series Technical File" should indicate that the cited article is from Shenzhen Shumatt Technology Co., Ltd., Any actions failure to follow above conditions to use "AP63813BN Injector MTU Series Technical File" will violate the "Copyright Law of the People's Republic of China" and other laws and regulations and the provisions of relevant international conventions.

Mob/WhatsApp: +86 13410541523 Email: <u>ruby@shumatt.com</u> © 2024 Shenzhen Shumatt Technology Co., Ltd

أتأسله

Tel: +8675523215133 Website : <u>www.shumatt.com</u>