

5491600 Injector XPI Series Technical File

SKU1: G1K30005491600





A INFIT

SHUMAT

Shenzhen Shumatt Technology Co., Ltd

INFIT

SHUMMIT

Зh

Зh

5491600 Injector XPI Series Technical File

content

A IMPIT I	1. 5491600 Injector Introduction	
3712	1.1. 5491600 Injector Basic Information	2
	1.2. 5491600 Injector Common Part Number	2
Time	1.3. 5491600 Injector Parameter	2
SHUM	1.4. 5491600 Injector Specifications and Dimensions	2
	1.5. 5491600 Injector Quality Control	
TI	1.6. 5491600 Injector Customized Service	3
SHUMM .	1.7. 5491600 Injector Packing List and Package Size	3
	1.8. 5491600 Injector Testing Standard and Certificate	5
-	1.9. 5491600 Injector Warranty Instructions	
-HUMPY'	1.10. 5491600 Injector Manufacturer	7
21	2. 5491600 Injector Technical Support	7
4	2.1. 5491600 Injector Part Number Location	7
a unifit '	2.2. 5491600 Injector Installation	8
372	2.3. 5491600 Injector Reasons for Not Working Normally	9
	2.4. 5491600 Injector Causes of Being Damaged	9
ITIMIN	2.5. 5491600 Injector Technical Support Obtaining Methods	10
SHOW	3. 5491600 Injector Purchase and Delivery	10
	3.1. 5491600 Injector Purchase Payment Term	10
TI	3.2. 5491600 Injector Main Sales Markets	10
SHUMM	3.3. 5491600 Injector Declaration Requirements	10
	3.4. 5491600 Injector Shipping Ways	
-	3.5. 5491600 Injector Lead time	10
-HUMPY'	3.6. 5491600 Injector Logistics Time for Destination Out of China's Areas	
31.	3.7. 5491600 Injector Packing	12
4	4. 5491600 Injector Storage Standard	13
I TRANLO	5. Company Information	13
3112	5.1. Company Introduction	14
	5.2. Sales-men's Contact Information	14
Trime	6. Copyright Statement	15

AINT Mob/WhatsApp: +86 13410541523 Email: ruby@shumatt.com © 2025 Shenzhen Shumatt Technology Co., Ltd

UNIT

UNIT

1

UNAT

UNIT

Tel: +8675523215133 Website Website : www.shumatt.com

5491600 Injector XPI Series Technical File

1. 5491600 Injector Introduction

SHUMATT

1.1. 5491600 Injector Basic Information

1.1. 5491600 Inje	ctor Basic Information	ITAMIC INFITT
Title	Common Rail 5491600 Injector XPI Series	Quality
SKU1	G1K30005491600	Re-manufactured
/		A A

1.2. 5491600 Injector Common Part Number

(1) Injector Exchange Information

	Injector Part Number			Re-	manufactu	ring Numb	er		001
Uni	5491600	SHUIII SH	Un	=HUIII	shum /	SHUM	3HUIII	51	

(2) Injector Application Information

3	Vehicle Brand	Car Model	Engine Number		
	For Cummins	Cummins			
				-	

(3) Injector Part Number Common Writing 5491600

1.3. 5491600 Injector Parameter

Adaptation System: Common Rail System Injector Series: XPI Series Injector Type: Electromagnetic

1.4. 5491600 Injector Specifications and Dimensions

Injector Size: 29cm* 11cm *6cm Injector Net Weight: 1200g Injector Gross Weight: 1290g Injector Quality: Re-manufactured Injector Package Size: 31cm*13 cm *8 cm Injector Type: High Pressure Common Rail Injector **Injector MOQ: 4 Pieces**

1.5. 5491600 Injector Quality Control

(1) Injector Testing

All injector spare parts are tested for electrical characteristics, accuracy, high temperature, low temperature, withstand voltage, leakage, durability, and various working conditions.

(2) Injector Assembling

For the quality control of the injector production and installation process, our company strictly follows the standard product installation data and product installation steps to install, such as injector stroke test, injector solenoid valve tightening torque, injector nozzle tightening torque.

(3) Injector Inspection

The factory inspection of the injector is undergone full inspection, random inspection, and batch

Mob/WhatsApp: +86 13410541523 Email: ruby@shumatt.com

Tel: +8675523215133 Website : www.shumatt.com

inspection three inspections. Different brands of test benches are used to test the same injector for more than three times for factory inspection, and the injector installation testing environment are progressed in dust-free workshop.

1.6. 5491600 Injector Customized Service

SHUMATT

(1) Injector's Customized Service Coverage: Meet the customized needs of OEM manufacturers for shell lettering, logo engraving, injector internal packaging, injector external packaging and labels customized, etc.



(2) Injector's Customized Service Requirements:

The quantity of customized injectors shall not be less than 10 pieces.

The quantity of customized injector packages shall not be less than 1000 pieces.

Customized products involve the need of specify logo, the OEM manufacturer needs to provide trademark authorization and the sample of logo image file.

Once the customized injector is sold, it cannot be returned or exchanged if there is no quality problem.

2	1) Injector Spare Pa	artsList 🧖	31	21.	31.	21	21. 3	21. 21.	31
	No.		1			2		3	
134	UMATT SAUMATT	Autor Shumatt	A	THE			Statement T		TIM
In	Unit Image	Autorit S		T			A R	27 77 78	T
11	Name	aumini Inj	ector assy	TT	Anti-ru	ist paper	vc	I Anti-Rust bag	nini Ti
11	Description	injector assy	y number: 54	91600		injectors from sting	Prevent	fuel injectors fro rusting	om
12	UMATT	AUMATT SHUT	INTT SHAIM	TT	NATT SHUMA	SHUMAIT	AUMATT	HUMPITT	NATT

1.7. 5491600 Injector Packing List and Package Size

Mob/WhatsApp: +86 13410541523 Email: ruby@shumatt.com

15		Shenzhen Shumatt	Technology Co., Ltd	Unur. 247un. 247un. 24
<	No.	4	5	6
In	Aluter, SHINE, S	Anner, Stanner, Stanner, Sta	and stranger attantes a	Villes, Standar, Standar, Sta
11	Image	ALME ETERSON SHU		AUMPITI SHUMPITI
11	Name	Lining	Fuel injector packaging box	Automati Stautomati Stautomati
in la	Description	Prevent the injector from being damaged by external forces	Place the injector and injector accessories	Automit Standard Standard Sta

Minors are forbidden to use the injector assembly, O-ring, nozzle protective cover, fuel injector housing protective cover, oil return protective cover, VCI anti-rust bag, and air bubble bag to avoid personal injury.

• O-ring and nozzle gasket are disposable installation accessories, and need to be replaced for re-installation.

The nozzle protective cover, the injector housing protective cover, and the oil return protective cover are recyclable accessories and can be recycled.

A VCI anti-rust bags and bubble bags are non-degradable materials, please dispose them properly

after using.

SHUMA

SHUMA

A The injector and the installation parts should be coated with appropriate sealing oil during

UMA

installation.

(2) Injector Box Size

Mob/WhatsApp: +86 13410541523 Email: <u>ruby@shumatt.com</u> © 2025 Shenzhen Shumatt Technology Co., Ltd

UMAT

UNIT

Tel: +8675523215133 Website : <u>www.shumatt.com</u>

HUMATT	No.	AUTOR		Name jector Box	- A JITTA	- Umr	Injec	tor Package 31*13	e Size(cm 3*8)	. a initi	T
SHUMPITT	HUMPIT	SHL.	3HUM	SHUM	当村しい	SHLow	SHLUM	SHOW	SHOW	SHUMPT	SHUMPT	T 5H
SHUMPIT	HUMPT	_								ment	SHUMAT	T
SHUMPITT	AUMPATT									ant	SHUMAT	T
SHUMPITT	HUMMIT									and the second	SHUMM	T
HUMMATT	HUMPIT									mini	T	T
SHUMPITT	HUMPT									arit	SHUMAT	T
71. 2		SHUMA	IN .	Shenzh	en Shui	matt Te	chnolog	gy Co., L	.td	SHUMAN	21	Ш

1.8. 5491600 Injector Testing Standard and Certificate

Shumatt can provide the factory quality inspection test report of each injector to ensure that each delivered injector meets the engine performance indicators.

Mob/WhatsApp: +86 13410541523 Email: <u>ruby@shumatt.com</u> © 2025 Shenzhen Shumatt Technology Co., Ltd

AUMAT

UMAT

UMAT

UMAT

UNIT

Tel: +8675523215133 Website : <u>www.shumatt.com</u> 3h

Зh

Зh

3H

3h

Ξh

3h

SHUMF

BOTEN		测试	报告	4.05.2019	10:42:05
承伸企业:					
电话:		284	t;		
传真:		407	8人:		
安中教師:					
tið.		228	自举位:		
倚真:		WF	9156:		
旅路说话:					
韵料名称:	的 体实际				
型号 零件号:					
lika:					
10702100		检测	结果		
121609: C	005000-6511 動能時間的	·	RÉDIX OF	8:0×10	
LEAR TEST:	32	4	65	30.84114.6	~
Fad:	37		157	a ++ ++ + +	1
WARM	38	147 3 ± 16 5	0		
Max:	2013	218 5±14.4		····· <u>p</u> ·····	~
n.	28.4	34.6±8.5	()		4
U.;	14.1	157248	69		~
VE:	47	4.5.±1.8	63		*
ei Lles Lle	s Jew Jes L	las _ar [as	法程序调查。		

1.9. 5491600 Injector Warranty Instructions

(1) Product Warranty Conditions and Instructions

It is necessary to provide pictures, videos, or test reports detected by the injector inspection equipment when the injector is abnormal during use as evidence to feed back to the salesman.

Abnormal conditions are properly explained such as: 1.Smoke, 2. Engine shake, 3. Difficulty starting the engine, 4. Engine noise, 5. oil leakage etc.

(2) Injector Warranty Coverage

Within 15 days after customer receives the 5491600 injector, if there is a performance failure and the product has no appearance damage, customer can choose to replace it or repair it;

If the 5491600 injector has performance problems during the warranty period (6-12 months), and it is confirmed that it is product's problems after testing, you can contact our salesmen to replace the same model or a reworked product with the same performance for free;

If the injector house has obvious scratches, it can only be repaired and it will be returned as it is if the product is confirmed to be fault-free.

Tips: For products not covered by warranty, our company can provide paid maintenance services. For products after paid repaired, the same performance problem will have a free warranty period within 3 months from the date of repairing.

(3) Injector Out of Warranty Coverage

Mob/WhatsApp: +86 13410541523 Email: ruby@shumatt.com

Tel: +8675523215133 Website : www.shumatt.com

1) The warranty period has expired.

SHUMATT

② Injector failure caused by high temperature, high pressure, humidity, rain and snow, saline-alkali land, earthquake, and used in abnormal environment.

③ Customer disassembles or repairs the injector personally resulting in damage to the injector.

④ Injector damage caused by man-made reasons (throwing, strong magnetic field magnetization, set

fire).

⑤ Injector failure or injector damage caused by non-injector design, technology, manufacturing, quality, and other issues.

6 Injector failure due to system pressure exceeding system approved pressure

O Injector failure caused by system voltage exceeding approved voltage.

8 Injector failure caused by impurities (water, lead, aluminum powder, iron powder, sulfide) in the system fuel exceeding the standard requirements.

Injector failure caused by not installing according to the tightening torque specified in the vehicle engine maintenance manual (the tightening torque is too large or too small).

0 Injector failure caused by not following the installation angle specified in the vehicle engine maintenance manual.

11 Injector failure caused by not following the cleaning requirements specified in the vehicle engine maintenance manual.

12 Injector failure caused by failure to replace consumable parts as specified in the vehicle engine maintenance manual.

13 Injector failure caused by not complying with the intake system fit clearance and exhaust system fit clearance requirements specified in the vehicle engine maintenance manual.

14 Failure to replace the consumable parts and the fitting clearance of the oil inlet system pipeline and the injector connection in accordance with the fuel intake system specified in the vehicle engine maintenance manual.

1.10. 5491600 Injector Manufacturer

Injector's Manufacturer: Shenzhen Shumatt Technology Co., Ltd

2. 5491600 Injector Technical Support

2.1. 5491600 Injector Part Number Location

1) E.g.: See the injector part number as follows

The Th	1	The second	T		TT.	-TT	T
No.				Nar	ne		
А	~		~ ~	Bran, logo	, coding		

Mob/WhatsApp: +86 13410541523 Email: <u>ruby@shumatt.com</u> © 2025 Shenzhen Shumatt Technology Co., Ltd Tel: +8675523215133 Website : <u>www.shumatt.com</u>

Shenzhen Shumatt Technology Co., Ltd



2.2. 5491600 Injector Installation (1) 5491600 Injector Installation Precautions:

The replacement of the injector must strictly follow the electrical system, the approved pressure of the low-pressure fuel intake system, the approved pressure of the high-pressure fuel circuit system, and fuel system replacement consumables requirements (including the low-pressure fuel circuit system filter and the high-pressure fuel circuit) specified in the vehicle engine maintenance manual.

A Strictly follow the operation manual of replacement of wearing parts of the fuel system, cleaning

requirements for the connection between the fuel system and the injector, the fitting clearance of the injector connection, the installation angle and tightening torque of the injector, the fitting clearance of the intake system, and the fitting clearance of the exhaust system, so that to ensure the service life of the engine and the normal operation of the injector.

When installing the injector on the engine, it is necessary to clean the engine block, cylinder head and other parts connected to the injector, and ensure that there is no dust, carbon deposits, water, rust spots, etc.

Before installing, check whether the injector nozzle gasket has been replaced and installed on the injector.

When installing the injector, apply lubricant between the injector, injector nozzle sealing gasket and O-

Mob/WhatsApp: +86 13410541523 Email: <u>ruby@shumatt.com</u> © 2025 Shenzhen Shumatt Technology Co., Ltd Tel: +8675523215133 Website : <u>www.shumatt.com</u>

A If a new gasket is not replaced, it can lead to: deformation of the tight cap of nozzle, deformation of

nozzle, deformation of nozzle orifice, oil leakage and air leakage, which will cause serious damage to the injector and nozzle to break and cause damage to the engine.

When installing the injector on the engine, please carefully check the components related to the installation of the injector to ensure they are not deformed, such as the injector pressure plate, screw, injector rod and other accessories, and install it in strict accordance with the operation steps of the engine maintenance manual.

It is forbidden to operate the bare injector for a long time in an environment with serious dust pollution and corrosion to iron products.

A It is forbidden to operate the bare injector for a long time in a strong magnetic field environment.

2.3. 5491600 Injector Reasons for Not Working Normally

- (1) There is air in the oil circuit of the engine fuel system.
- (2) Vehicle fuel injector fuel supply system is abnormal.

SHUMATT

- (3) Engine common rail system oil leakage or pressure limiting valve damage.
- (4) There is a short circuit, cutting out and poor contact in the wiring harness connected to the injector of the vehicle.
- (5) The long-term placement of the injector causes the anti-rust oil to solidify, and the internal components are stuck or the oil holes are blocked.

A Before installing, carefully check whether other components in the common rail system except the injector are damaged to prevent the injector from not working properly after being replaced.

2.4. 5491600 Injector Causes of Being Damaged

- (1) Didn't operate properly according to engine maintenance manual during disassembly or installation, resulting in damage to the injector.
- (2) The fuel oil used for the vehicle does not meet the standard cause damage to the injector, such as: the water content in the fuel oil exceeds the standard, iron powder, aluminum powder, sulfide impurities exceed the standard, etc.
- (3) The engine is not regularly maintained according to the engine maintenance manual (please refer to the vehicle maintenance manual for the maintenance mileage). For example, failure to replace the lubricating oil of the engine system for a long time will cause abnormal wear of the engine, excessive exhaust gas volume or a large amount of carbon deposits inside the engine. The filter is not replaced during maintenance or the replaced filter cannot reach the original filter standard. all above reasons can cause damage to the injector.
- (4) The abrasion of the injector produces iron powder and aluminum powder enter the injector and cause damage to the injector.
- (5) The deformation and abrasion of fuel tank result in iron powder or aluminum powder entering the injector and causing damage to the injector.

Mob/WhatsApp: +86 13410541523 Email: ruby@shumatt.com Tel: +8675523215133 Website : <u>www.shumatt.com</u>

- (6) The injector is damaged due to replacement or adjustment of the relevant parts of the injector. For example, the valve clearance does not meet the standard after the engine is repaired, the replacement or modification of the wiring harness connected to the injector fails to meet the original standard.
- (7) The engine is overheated and overloaded for a long-time working result in damage to the injector.
- (8) The injector will be damaged naturally at the end of its working life.
- (9) The injector is magnetized (injector parts' magnetic exceeded) causing the injector to not work properly.

Before replacing the injector, please check the engine parts carefully according to the engine maintenance manual to avoid the injector being damaged again after replacement.

2.5. 5491600 Injector Technical Support Obtaining Methods

- (1) Injector Technical File , visit <u>http://shumatt.com</u> to get the technical file.
- (2) Injector Technical Videos

SHUMATT

Facebook: Visit https://www.facebook.com/hison.li to get the technical videos, constantly follow can get more information.

YouTube: https://www.youtube.com/channel/UCByvYBx7VjV mAfxh Hu-aw to get the technical videos, constantly follow can get more information.

Shumatt: Visit http://shumatt.com to get the technical videos.

(3) Injector Information Query Software

TruckBook Parts EPC APP, Android/Apple App Store download and install, visit <u>http://shumatt.com</u> to get the download and installation tutorial

(4) Search The injector test data through TruckBook Parts EPC APP.

3. 5491600 Injector Purchase and Delivery

3.1. 5491600 Injector Purchase Payment Term Payment Terms: T/T, PayPal, Alipay, WeChat

Please contact our salesmen for specific payment information.

3.2. 5491600 Injector Main Sales Markets

Injector main sales markets: Asia, Europe, North America, South America, Africa etc.

3.3. 5491600 Injector Declaration Requirements

Shumatt can assist customers to provide the following documents for import customs clearance: contract, invoice, packing list, bill of lading, insurance policy, certificate of origin, etc.

3.4. 5491600 Injector Shipping Ways

Destination in China Areas: SF Express, Debon Express, the corresponding logistics company can be provided according to customer requirements in special cases.

Destinations Out of China's Areas: DHL, UPS, FedEx, TNT air, ocean or other shipping methods required by customers.

3.5. 5491600 Injector Lead time

Lead time: Send out within 3 – 7 working days after receiving payment (Except for special products and special cases)

Mob/WhatsApp: +86 13410541523 Email: ruby@shumatt.com

Tel: +8675523215133 Website : www.shumatt.com

3.6. 5491600 Injector Logistics Time for Destination Out of China's Areas

DHL Logistics Time :

SHUMATT

Country or Region of Departure	Hong Kong, China	Other Countries or Regions of Asia	Australia and New Zealand	Europe	America	Other Countries
China's Mainland	7 Days	7 Days	8 Days	8 Days	8-12 Days	7-10 Days

UPS Logistics Time: Country or Region of Departure: China's Mainland

Country of Destination	Estimated Arrival Time	Country of Destination	Estimated Arrival Time	Country of Destination	Estimated Arrival Time
Japan	3 Days	UK UK	5-7Days	Egypt	5-7 Days
Turkey	5-7 Days	Singapore	3 Days	Switzerland	5-7 Days
Bahrain	5-7 Days	Latvia	7-10 Days	New Zealand	7-10 Days
Sri Lanka	5-7 Days	Thailand	3 Days	Austria	5-7 Days
Romania	5-7 Days	Vietnam	3-5 Days	Estonia	5-7 Days
Malaysia	3-5 Days	Israel	5-7 Days	Mexico	7-10 Days
France	5-7 Days	America	5-7 Days	United Arab Emirates	5-7 Days
Italy	5-7 Days	Netherlands	5-7 Days	Bengal	7-10 Days
Lebanon	5-7 Days	Philippine	3-5 Days	Greece	7-10 Days
South Korea	3 Days	Spain	5-7 Days	Myanmar	5-7 Days
Canada	5-7 Days	Germany	5-7 Days	Saudi Arabia	7-10 Days
Portugal	5-7 Days	Australia	5-7 Days	South Africa	7-10 Days
Denmark	5-7 Days	Belgium	5-7 Days	Ukraine	7-10 Days
India	7-10 Days	Qatar	7-10 Days	Poland	5-7 Days
Indonesia	3-5 Days	Morocco	7-10 Days	Pakistan	7-10 Days
Kuwait	7-10 Days	HUMMA SKUMMA SH	min' stamm	shumm'shumm's	Harmin' St

A The logistics time is for reference only and is subject to the actual arrival.

Mob/WhatsApp: +86 13410541523 Email: <u>ruby@shumatt.com</u> © 2025 Shenzhen Shumatt Technology Co., Ltd Tel: +8675523215133 Website : <u>www.shumatt.com</u>

11/14

SHIMM

3.7. 5491600 Injector Packing

Domestic express packaging: Usually wrapped in waterproof scotch tape, such as picture No.1. **International express packaging:** Wrapped with waterproof yellow tape After wrapping the black protective film, such as picture No. 2.

Pallet Shipping: Use fumigation free and recycling trays that meet export requirements, and use white wrapping protective film to wrap and bind with cable ties for the outside, such as picture No. 3, also, the products can be packaged according to customers' requirements.

A The packing tray is made of plastic and can be recycled.

Transparent tape, yellow tape, black wrapping protective film, white wrapping protective film are non-degradable materials, please dispose of them properly.

A Minors are prohibited from using transparent tape, yellow tape, black wrapping protective film, and white wrapping protective film to avoid personal injury.





SHUMF

Pic No. 1 Domestic express packaging: Wrapped with Transparent tape Pic No. 2 International express packaging: Wrapped with yellow tape after wrapping black protective film

1 min



SHUMAT

Pic No. 3

Pallet Shipping: Use pallet that meet export requirements, and use white wrapping protective film to wrap and bind with cable ties

Mob/WhatsApp: +86 13410541523 Email: <u>ruby@shumatt.com</u> © 2025 Shenzhen Shumatt Technology Co., Ltd Tel: +8675523215133 Website : <u>www.shumatt.com</u>

4. 5491600 Injector Storage Standard

(1) Choose a suitable storage place

SHUMATT

The warehouse and cargo yard where the injector is stored should be kept clean and dry, and away from the factory buildings that generate harmful gases and dust; do not mix with acids, alkali, salt and other substances; the storage place should have a good drainage system; the cargo yard should be flattened with gravel or furnace ash etc. to enhance the water permeability of the surface layer to keep the reservoir area dry.

(2) Strict requirements of warehousing

Strict inspections should be carried out when the injectors are put into storage, the surface cleaning work should be done well to remove water traces, oil stains, ash, and other dirt, remove the rust and do antirust treatment in time. Packaged injectors must be protected from damage.

(3) Keep the warehouse dry and preventing moisture

The relative humidity is usually below 70% for the injectors placed in the room, and the corrosion of the injectors is significantly reduced.

Injectors must be stored in the warehouse, and they are forbidden to store in the same warehouse with commodities with high water content.

(4) Stack Properly

After the injector is exposed to rain, the corrosion rate will increase significantly. The purpose of sealing is to isolate the injector from rainwater and humid air, so the warehouse window should be checked in time to avoid rainwater entering the warehouse

If the injector package is damaged, it should be repaired or replaced; when the package is damp, the packaging material should be dried; if the original anti-corrosion and oil applied at the factory is found to be damaged or dried up, it should be cleaned and re-applied oil in time.

It is forbidden to leave the injector exposed in the air for a long time.

A It is forbidden to store acids, alkali, salt, and other substances together with the injector.

A The unpacked injector must be rust-proof during secondary storage.

5. Company Information

Mob/WhatsApp: +86 13410541523 Email: <u>ruby@shumatt.com</u> © 2025 Shenzhen Shumatt Technology Co., Ltd Tel: +8675523215133 Website : <u>www.shumatt.com</u>

Office LocationsGlobal Exhibitions

SHUMATT

5.1. Company Introduction Chinese Name: 深圳市舒马特科技有限公司

English Name: Shenzhen Shumatt Technology Co., Ltd

Mob Phone/WeChat: +86-13410541523

HK Telephone: +852-67653519

Telephone: +86-755-23215133

Email: ruby@shumatt.com

Website: www.shumatt.com

Shenzhen Office: 11-12, Floor 14, Building 13, Qinchengda Building, Exit A, Honglang North Subway Station, Bao'an District, Shenzhen, China's Mainland

Shenzhen Office: Exit C, Qiao Touxi Metro Station, NO. 66 Chongqing Road, Fuhai Avenue, Bao'an District, Shenzhen, China Mainland

Hong Kong Office: Jianfa Street Industrial Zone, Tuen Mun, New Territories, Hong Kong, China

• After-sales Service Address: Please contact our salesmen to obtain and provide the corresponding product maintenance reasons (Reference: <u>1.9. 5491600 Injector Warranty Instructions</u>)

5.2. Sales-men's Contact Information

No.	Name WeChat/WhatsApp		Email		
1 31	Ruby	+86-13410541523	ruby@shumatt.com		
2 Ivy		+86-18025299821	sales@shumatt.com		
-1131	Rebecca	+86-18025349821	sales01@shumatt.com		

Mob/WhatsApp: +86 13410541523 Email: <u>ruby@shumatt.com</u> © 2025 Shenzhen Shumatt Technology Co., Ltd Tel: +8675523215133 Website : <u>www.shumatt.com</u>

4	Janny	+86-18028749821	sales02@shumatt.com
SHUTS SH	Sam	+86-13316859821	Sales8@shumatt.com
6	Natalie	+86- 18938945856	sales 15@shumatt.com
7	Ada	+86-1342286353	sales5@shumatt.com
3HU 8 3H	Hison Li	+86-18318811871	web@shumatt.com
9	Mecca	+86-18938948618	sales11@shumatt.com
10	Eric	+86 18319033618	sales3@shumatt.com
SHUMIT SH	Wayne (Joaquín en español)	+86-13316959821	wayne@shumatt.com
12	Sylvia	+86 18312499884	sales6@shumatt.com
SHUMMA SK	Visit http://shumatt.co	m to obtain the latest information	of salesmen
2. 2.	PS: Shumatt's sales-r	men's emails are all end with @sh	umatt.com

6. Copyright Statement

SHUMATT

The copyright of any contents (including but not limited to parameters, data, text, charts, images, sounds, or videos, etc.) provided in "5491600 Injector XPI Series Technical File" belong to Shenzhen Shumatt Technology Co., Ltd. Without the prior written permission of Shenzhen Shumatt Technology Co., Ltd., you are not allowed to modify any contents in "5491600 Injector XPI Series Technical File" in any way. At the same time, any conditions to spread, re-post, display the contents of "5491600 Injector XPI Series Technical File" should indicate that the cited article is from Shenzhen Shumatt Technology Co., Ltd., Any actions failure to follow above conditions to use "5491600 Injector XPI Series Technical File" will violate the "Copyright Law of the People's Republic of China" and other laws and regulations and the provisions of relevant international conventions.

Mob/WhatsApp: +86 13410541523 Email: <u>ruby@shumatt.com</u> © 2025 Shenzhen Shumatt Technology Co., Ltd Tel: +8675523215133 Website : <u>www.shumatt.com</u> 3h